

## Product data sheet

### Characteristics

## 2510KR2H

Switch, manual, 30A, 3 pole, 10 HP at 575 VAC, three phase, toggle operated, no indicator, NEMA 7/9, two conduit opening



### Main

|         |                           |
|---------|---------------------------|
| Product | Single Unit Manual Switch |
| Type    | K                         |

### Complementary

|                        |                                                                                                                          |
|------------------------|--------------------------------------------------------------------------------------------------------------------------|
| Current Rating         | 20 A                                                                                                                     |
| Cable Entry            | 0.75 NPT (top and bottom)                                                                                                |
| Horsepower Rating      | 2 Hp 115 V AC<br>1 Hp 90 V DC<br>2 Hp 115 V DC<br>1.5 Hp 230 V DC<br>7.5 Hp 230 V AC<br>10 Hp 460 V AC<br>10 hp 575 V AC |
| Maximum Voltage Rating | 600 V AC<br>230 V DC                                                                                                     |
| Number of Poles        | 3P                                                                                                                       |
| Control Unit Type      | Toggle                                                                                                                   |
| Number of Phases       | 3 phase                                                                                                                  |
| Pilot Light            | No indicator                                                                                                             |
| Starter Type           | Non reversing                                                                                                            |
| Electrical Connection  | Screw clamp terminals                                                                                                    |
| Wire Gauge             | AWG 14...AWG 10 copper                                                                                                   |
| Maximum Height         | 6.36 in (161.54 mm)                                                                                                      |
| Maximum Width          | 3.95 in (100.33 mm)                                                                                                      |
| Maximum Depth          | 4.35 in (110.49 mm)                                                                                                      |

### Environment

|                       |                                                             |
|-----------------------|-------------------------------------------------------------|
| Certifications        | UL listed file E58760 CCN NPXZ<br>CSA LR26817 class 3218 04 |
| NEMA Enclosure Rating | NEMA 3R/7/9 cast aluminium standard size                    |

### Ordering and shipping details

|                     |                          |
|---------------------|--------------------------|
| Category            | 21102 - 2510,2511,2512 K |
| Discount Schedule   | CP1                      |
| GTIN                | 00785901554646           |
| Package weight(Lbs) | 3.53 lb(US) (1.60 kg)    |
| Returnability       | Yes                      |
| Country of origin   | MX                       |

Offer Sustainability

|                       |                                                                                                                          |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------|
| REACH Regulation      |  <a href="#">REACH Declaration</a>      |
| REACH free of SVHC    | Yes                                                                                                                      |
| EU RoHS Directive     | Not compliant                                                                                                            |
| China RoHS Regulation |  <a href="#">China RoHS Declaration</a> |

Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|