



## Main

Accessory / separate part category	Cabling accessories
Accessory / separate part type	Connector
Electrical connection	Elbowed female connector M23, 19 pins
Collar material	Metal
Status LED	Without
Cable connection	Solder terminal 0.00 in <sup>2</sup> (1 mm <sup>2</sup> ) 0.35...0.47 in (9...12 mm)

## Complementary

Cable gland type	Pg 13.5
Cable connector fixing	Screw-on
[Ue] rated operational voltage	60 V AC 75 V DC
Line Rated Current	7.5 A
Enclosure material	Metal
Minimum insulating resistance	10000000 GΩ
Contact resistance	5000 μOhm
Net Weight	0.33 lb(US) (0.15 kg)

## Environment

IP degree of protection	IP65
Ambient air temperature for operation	-13...230 °F (-25...110 °C)



## Ordering and shipping details

Category	22499 - SENSORS ACCESSORIES
Discount Schedule	DS2
GTIN	03389110833911
Nbr. of units in pkg.	1
Package weight(Lbs)	0.32 lb(US) (0.15 kg)
Returnability	No
Country of origin	DE

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.18 in (3 cm)
Package 1 width	2.76 in (7 cm)
Package 1 Length	3.54 in (9 cm)
Unit Type of Package 2	S01
Number of Units in Package 2	20
Package 2 Weight	7.71 lb(US) (3.498 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	5.91 in (15 cm)
Package 2 Length	15.75 in (40 cm)


Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes

Contractual warranty

Warranty	18 months
----------	-----------

## Dimensions



(1) Cable gland: no. 13 metal (Pg 13.5)

Connections and Schemes

