



Main

Product or component type	Starter
Type	S
Control Circuit Type	Common control circuit

Complementary

Control Circuit Voltage	220 V AC 50 Hz 240 V AC 60 Hz
Motor starter type	Non reversing
Current Rating	45 A
Number of Poles	2P
Number of Phases	1 phase
Horsepower Rating	3 HP 115 V AC 7.5 HP 230 V AC
Maximum Voltage Rating	600 V AC
Control Units	2 momentary push-buttons (START-STOP)
Thermal overload type	Melting alloy 1
Electrical connection	Screw clamp terminals
NEMA size	2
Maximum Height	16.30 in (414 mm)
Maximum Depth	8.62 in (219 mm)
Maximum Width	9.84 in (250 mm)



Environment

Enclosure Type	NEMA 3R painted sheet steel
Product certifications	UL Listed NEMA CSA

Ordering and shipping details

Category	21192 - 8502,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
Package weight(Lbs)	27.91 lb(US) (12.66 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------