



### Main

|                               |                                                                                                                                                                               |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range of product              | Harmony XB7                                                                                                                                                                   |
| Product or component type     | Push-button                                                                                                                                                                   |
| Device short name             | XB7                                                                                                                                                                           |
| Mounting diameter             | 0.87 in (22 mm)                                                                                                                                                               |
| Sale per indivisible quantity | 10                                                                                                                                                                            |
| IP degree of protection       | IP20 IEC 60529 rear face)<br>IP65 IEC 60529 front face)                                                                                                                       |
| Shape of signaling unit head  | Round                                                                                                                                                                         |
| Type of operator              | Spring return                                                                                                                                                                 |
| Operator profile              | White flush, left arrow black)                                                                                                                                                |
| Contacts type and composition | 1 NO + 1 NC                                                                                                                                                                   |
| Connections - terminals       | Screw clamp terminals, <= 2 x 1.5 mm <sup>2</sup> with cable end EN/IEC 60947-1<br>Screw clamp terminals, 1 x 0.34...2 x 2.5 mm <sup>2</sup> without cable end EN/IEC 60947-1 |
| Device presentation           | Monolithic product                                                                                                                                                            |

### Complementary

|                                        |                                                                                                                                                                                   |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CAD overall width                      | 1.14 in (29 mm)                                                                                                                                                                   |
| CAD overall height                     | 1.14 in (29 mm)                                                                                                                                                                   |
| CAD overall depth                      | 2.03 in (51.5 mm)                                                                                                                                                                 |
| Terminals description ISO n°1          | (13-14)NO<br>(21-22)NC                                                                                                                                                            |
| Net Weight                             | 0.05 lb(US) (0.021 kg)                                                                                                                                                            |
| Device mounting                        | Fixing hole 0.89 in (22.5 mm) 22.3 +0.4/0 EN/IEC 60947-1                                                                                                                          |
| Fixing center                          | >= 30 x 40 mm support panel) metal 0.04...0.24 in (1...6 mm)<br>>= 30 x 40 mm support panel) plastic 0.08...0.24 in (2...6 mm)                                                    |
| Fixing mode                            | Fixing nut beneath head 17.70...21.24 lbf.in (2...2.4 N.m)                                                                                                                        |
| Contact operation                      | Slow-break                                                                                                                                                                        |
| Positive opening                       | With NC contact EN/IEC 60947-5-1 appendix K                                                                                                                                       |
| Mechanical durability                  | 1000000 cycles                                                                                                                                                                    |
| Tightening torque                      | 7.08...10.62 lbf.in (0.8...1.2 N.m) EN 60947-1                                                                                                                                    |
| Shape of screw head                    | Cross JIS No 1<br>Cross Philips no 1<br>Cross pozidriv No 1<br>Slotted flat Ø 4 mm<br>Slotted flat Ø 5.5 mm                                                                       |
| Short-circuit protection               | 4 A cartridge fuse gG EN/IEC 60947-5-1                                                                                                                                            |
| [Ui] rated insulation voltage          | 250 V 3)EN/IEC 60947-1                                                                                                                                                            |
| [Uimp] rated impulse withstand voltage | 4 kV EN/IEC 60947-1                                                                                                                                                               |
| [Ie] rated operational current         | 0.1 A 250 V, DC-13, R300 EN/IEC 60947-5-1<br>0.22 A 125 V, DC-13, R300 EN/IEC 60947-5-1<br>0.3 A 240 V, AC-14, D300 EN/IEC 60947-5-1<br>0.6 A 120 V, AC-14, D300 EN/IEC 60947-5-1 |

|                        |                                                                                                                                                                                                                                                           |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Electrical durability  | 1000000 Cycles, DC-13, 0.3 A 24 V 216000 cyc/mn 0.5 EN/IEC 60947-5-1 appendix C<br>1000000 Cycles, AC-15, 0.03 A 230 V 216000 cyc/mn 0.5 EN/IEC 60947-5-1 appendix C<br>1000000 cycles, AC-15, 0.09 A 240 V 108000 cyc/mn 0.5 EN/IEC 60947-5-1 appendix C |
| Electrical reliability | $\Lambda \leq 10\exp(-6)$ 17 V, 5 mA EN/IEC 60947-5-4                                                                                                                                                                                                     |

## Environment

|                                       |                                                                                                                    |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------|
| Protective treatment                  | TH                                                                                                                 |
| Ambient air temperature for storage   | -40...158 °F (-40...70 °C)                                                                                         |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C)                                                                                         |
| Overvoltage category                  | Class II IEC 61140                                                                                                 |
| NEMA degree of protection             | NEMA 12 UL 50 E<br>NEMA 3 UL 50 E                                                                                  |
| Standards                             | CSA C22.2 No 14<br>JIS C8201-5-1<br>EN/IEC 60947-5-1<br>UL 508<br>EN/IEC 60947-1<br>JIS C8201-1                    |
| Product certifications                | GOST<br>CCC                                                                                                        |
| Vibration resistance                  | 5 gn 2...500 Hz)IEC 60068-2-6                                                                                      |
| Shock resistance                      | 50 gn 11 ms) half sine wave acceleration IEC 60068-2-27<br>30 gn 18 ms) half sine wave acceleration IEC 60068-2-27 |

## Ordering and shipping details

|                       |                               |
|-----------------------|-------------------------------|
| Category              | 22464 - PUSHBUTTONS, XB7-22MM |
| Discount Schedule     | CS2                           |
| GTIN                  | 00785901537311                |
| Nbr. of units in pkg. | 10                            |
| Package weight(Lbs)   | 0.04 lb(US) (0.02 kg)         |
| Returnability         | No                            |
| Country of origin     | ID                            |

## Packing Units

|                  |          |
|------------------|----------|
| Package 1 Height | 0.530 dm |
| Package 1 width  | 0.300 dm |
| Package 1 Length | 0.300 dm |

## Offer Sustainability

|                            |                                                                                                                                                                                      |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| REACH free of SVHC         | Yes                                                                                                                                                                                  |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)  <a href="#">EU RoHS Declaration</a> |
| Toxic heavy metal free     | Yes                                                                                                                                                                                  |
| Mercury free               | Yes                                                                                                                                                                                  |
| RoHS exemption information |  Yes                                                                                              |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>                                                           |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.                                                         |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|