



Main

Product or component type	Automatic switch
Range of product	PowerPact P
Trip unit technology	Magnetic

Complementary

Line Rated Current	1000 A
[Ue] rated operational voltage	600 V AC
Mounting mode	I-Line
Poles description	2P
Short-circuit withstand	65 KA 480 V UL 489 25 KA 600 V UL 489 100 kA 240 V UL 489
Breaking capacity code	J
Electrical connection	Lugs load I-Line connection line
AWG gauge	AWG 3/0...500 kcmil aluminium/copper)4
Terminal identifier	AL1200P25K
Magnetic tripping current	10000 A
Maximum Height	16.24 in (412.50 mm)
Maximum Width	16.54 in (420.12 mm)
Maximum Depth	14.49 in (368.05 mm)
Tightening torque	442.54 lbf.in (50 N.m) 0.15...0.37 in ² (95...240 mm ²) AWG 3/0...500 kcmil)

Environment

Product certifications	UL Listed IEC CSA
------------------------	-------------------------

Ordering and shipping details

Category	01210-PG,H,J,K,L,N I-LINE BREAKERS
Discount Schedule	DE2
Package weight(Lbs)	32.00 lb(US) (14.515 kg)
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------