

# Product data sheet

## Characteristics

# 70-178-2

Socket, Legacy general purpose relay  
accessory, 3PDT, 15A, 300 V, 11 pins, pins for  
printed circuit board, 788 S



### Main

Product range	Legacy
Product type	Socket
Product compatibility	Relay 788XBXR/XCXR
Number of terminals	11
Switch function	3PDT
Contact composition	3 NO + 3 NC

### Complementary

Line Rated Current	15 A
Rated voltage	300 V
Contact terminal arrangement	Mixed
Connections - terminals	Output pins for printed circuit boardsolid Output pins for printed circuit boardstranded
Fixing mode	By screws printed circuit boards
Net Weight	0.43 oz (12.1 g)
Width	1.50 in (38.1 mm)
Depth	1.37 in (34.8 mm)

### Environment

Ambient air temperature for storage	-40...221 °F (-40...105 °C)
Ambient temperature range - operational	-40...131 °F (-40...55 °C)
IP degree of protection	IP20
Flame retardance	UL94-V0
Product certifications	UL CSA CE RoHS

### Ordering and shipping details

GTIN	03606480277801
------	----------------

### Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.