



Main

Product or component type	Industrial Control Transformer
Power Rating	1000 VA 1500 VA
Primary Voltage	460 V 208 V 230 V
Secondary Voltage	115 V
Type	T

Complementary

Number of Phases	1 phase
Power Rating	1500 VA UL 1500 VA CSA 1500 VA NOM 1000 VA
Primary to Secondary Voltage	208 V 115 V 230 V 460 V
Temperature rise	115 °C
Electrical connection	Screw clamp terminals
Maximum Height	6.17 in (156.72 mm)
Maximum Width	7.06 in (179.32 mm)
Maximum Depth	7.17 in (182.12 mm)
Fingersafe Cover Compatibility	FSC2

Environment

Product certifications	UL Listed CSA
Enclosure Type	Not rated (open device)
Insulation temperature	356 °F (180 °C)

Ordering and shipping details

Category	16201 - 9070 T (NOT TF) 250-2000VA
Discount Schedule	CP8
GTIN	00785901322290
Nbr. of units in pkg.	1
Package weight(Lbs)	46.1 lb(US) (20.91 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Package 1 Height	12.30 in (31.242 cm)
Package 1 width	11.70 in (29.718 cm)
Package 1 Length	14.70 in (37.338 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Connections and Wiring Diagrams

Voltage Code	Voltages		Connections	
	Primary	Secondary	Primary	Secondary
D20	208/230/460	115	208: Connect to H1 and H2 230: Connect to H1 and H3 460: Connect to H1 and H4	Connect to X1 and X2

