



Overview

Presentation	A pre-assembled Micro Data Center includes: shock packaged rack, two UPS, two switched rack PDUs, NetBotz 250 with rack access handles, one temperature/humidity probe, blanking panels, and brush strip.
Lead time	Usually in Stock

Physical

Maximum Depth	42.13 in (107 cm)
Maximum Height	78.39 in (199.1 cm)
Maximum Mounting Depth	36.02 in (91.49 cm)
Minimum Mounting Depth	7.52 in (19.1 cm)
Marking	14 gauge EIA mounting rail 16 gauge front door 16 gauge post 18 gauge rear door 18 gauge roof 18 gauge side panels
Net Weight	620.01 lb(US) (281.23 kg)
Number of rack unit	42U
Permanent permissible load	2250 Lb(US) (1020.58 kg) dynamic 3000 lb(US) (1360.78 kg) static
Maximum Width	23.62 in (60 cm)

Ordering and shipping details

Package weight(Lbs)	874.99 lb(US) (396.89 kg)
---------------------	---------------------------

Packing Units

Package 1 Height	85.79 in (217.9 cm)
Package 1 width	43.50 in (110.5 cm)
Package 1 Length	52.01 in (132.1 cm)

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.