

Main

Device application	Power supply
Device short name	SK
Enclosure type	Standard environment enclosure indoor
Provided equipment	Vario V3 switch-disconnector
Range of product	Square D

Complementary

Depth	310.13 mm (12.21 in)
Design	Standard
Device mounting	Surface
Electrical connection	Screw clamp terminal
Maximum Height	340.36 mm (13.4 in)
Material	Copper winding
Mounting support	Panel
Phase	1 phase
Primary voltage	240 x 480 V
Rated power in VA	3000 VA
Rated voltage	120 V auxiliary power supply 120 V isolated
Secondary voltage	120 V
Temperature rise	115 °C
Maximum Width	375.92 mm (14.8 in)

Environment

Insulation temperature	356 °F (180 °C)
NEMA degree of protection	NEMA 1
Product certifications	UL listed file E61239 CSA LR37055

Ordering and shipping details

Category	21694-9070 SK
Discount Schedule	CP8
GTIN	00785901676614
Returnability	No

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------