

Main

Product or component type	Starter
Type	S
Control Circuit Type	Common control circuit

Complementary

Control Circuit Voltage	440 V AC 50 Hz 480 V AC 60 Hz
Motor starter type	Non reversing
Current Rating	90 A
Number of Poles	3P
Number of Phases	3 phase
Horsepower Rating	25 HP 200 V AC 30 HP 230 V AC 50 HP 460 V AC 50 HP 575 V AC
Maximum Voltage Rating	600 V AC
Control Units	No control units
Thermal overload type	Solid state Motor Logic class 10/20
Electrical connection	Screw clamp terminals
NEMA size	3
Maximum Height	11.10 in (282 mm)
Maximum Depth	6.50 in (165 mm)
Maximum Width	5.47 in (139 mm)

Environment

Enclosure Type	Not rated (open device)
Product certifications	NEMA UL Listed CSA

Ordering and shipping details

Category	21193 - 8502,36 SE,SF(NOT S*R,T,W)
Discount Schedule	CP1
Package weight(Lbs)	17 lb(US) (7.71 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------