

VLSFH1

TeSys VLS - fuse holder for 3P switch
disconnectors (up to 32 A / 10.3 x 38 mm)

Main

Range	TeSys
Product name	TeSys VARIO LS
Device short name	VLSFH
Fuse size	10.3 x 38 mm
Product or component type	Fuse holder
Poles description	3P
Network type	AC

Complementary

Network frequency	50/60 Hz
Mounting support	DIN rail
[Ui] rated insulation voltage	690 V AC 50/60 Hz
[Ith] conventional free air thermal current	32 A 131 °F (55 °C)
Connections - terminals	Power circuit screw clamp terminals 0.02 in ² (10 mm ²) solid Power circuit screw clamp terminals 0.02 in ² (16 mm ²) flexible without cable end
Tightening torque	Power circuit 15.93...17.70 lbf.in (1.8...2 N.m) screw clamp terminals
Maximum Height	2.96 in (75.2 mm)
Maximum Width	2.07 in (52.5 mm)
Maximum Depth	3.15 in (80.1 mm)
Net Weight	0.29 lb(US) (0.132 kg)

Environment

Standards	IEC 60947-3
IP degree of protection	IP20 IEC 60529
Ambient air temperature for operation	-13...131 °F (-25...55 °C)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.