



## Main

|                               |                              |
|-------------------------------|------------------------------|
| Range of product              | Harmony XB5                  |
| Product or component type     | Head for key selector switch |
| Device short name             | ZB5                          |
| Bezel material                | Plastic colour plated white  |
| Mounting diameter             | 0.87 in (22 mm)              |
| Head type                     | Standard                     |
| Sale per indivisible quantity | 1                            |
| Shape of signaling unit head  | Round                        |
| Type of operator              | Stay put                     |
| Operator profile              | Black key switch             |
| Operator position information | 2 positions 90°              |
| Type of keylock               | Dom 8D1                      |
| Key withdrawal position       | In any position              |

## Complementary

|                             |                                                                                                                                                                                                                                                                                                                                              |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CAD overall width           | 1.14 in (29 mm)                                                                                                                                                                                                                                                                                                                              |
| CAD overall height          | 1.14 in (29 mm)                                                                                                                                                                                                                                                                                                                              |
| CAD overall depth           | 2.83 in (72 mm)                                                                                                                                                                                                                                                                                                                              |
| Net Weight                  | 0.13 lb(US) (0.057 kg)                                                                                                                                                                                                                                                                                                                       |
| Mechanical durability       | 1000000 cycles                                                                                                                                                                                                                                                                                                                               |
| Station name                | XALD 1...5 cut-outs<br>XALK 2...5 cut-outs                                                                                                                                                                                                                                                                                                   |
| Electrical composition code | C4 6 single and double front mounting<br>C5 5 single front mounting<br>C6 5 single and double front mounting<br>C7 4 single front mounting<br>C8 4 single and double front mounting<br>C11 3 single front mounting<br>C3 6 single front mounting<br>SF1 3 single front mounting<br>SR1 3 single rear mounting<br>C15 1 single front mounting |
| Device presentation         | Basic element                                                                                                                                                                                                                                                                                                                                |

## Environment

|                                       |                                               |
|---------------------------------------|-----------------------------------------------|
| Protective treatment                  | TH                                            |
| Ambient air temperature for storage   | -40...158 °F (-40...70 °C)                    |
| Ambient air temperature for operation | -40...158 °F (-40...70 °C)                    |
| Overvoltage category                  | Class II IEC 60536                            |
| IP degree of protection               | IP66 IEC 60529<br>IP67                        |
| NEMA degree of protection             | NEMA 13<br>NEMA 4X                            |
| Resistance to high pressure washer    | 1015.26 psi (7000000 Pa) 131 °F (55 °C) 0.1 m |
| IK degree of protection               | IK06 IEC 50102                                |

|                        |                                                                                                                     |
|------------------------|---------------------------------------------------------------------------------------------------------------------|
| Standards              | EN/IEC 60947-5-4<br>JIS C8201-5-1<br>EN/IEC 60947-1<br>CSA C22.2 No 14<br>EN/IEC 60947-5-1<br>UL 508<br>JIS C8201-1 |
| Product certifications | CSA<br>BV<br>RINA<br>GL<br>DNV<br>UL Listed<br>LROS (Lloyds register of shipping)                                   |
| Vibration resistance   | 5 gn 2...500 Hz)IEC 60068-2-6                                                                                       |
| Shock resistance       | 30 gn 18 ms) half sine wave acceleration IEC 60068-2-27<br>50 gn 11 ms) half sine wave acceleration IEC 60068-2-27  |

## Ordering and shipping details

|                     |                    |
|---------------------|--------------------|
| Package weight(Lbs) | 2.33 oz (66.000 g) |
|---------------------|--------------------|

## Packing Units

|                  |                    |
|------------------|--------------------|
| Package 1 Height | 3.39 in (8.600 cm) |
| Package 1 width  | 1.30 in (3.300 cm) |
| Package 1 Length | 2.05 in (5.200 cm) |

## Offer Sustainability

|                            |                                                                                                                                                                                    |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)  <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes                                                                                                                                                                                |
| RoHS exemption information |  <a href="#">Yes</a>                                                                            |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>                                                         |