

# ZB4BW0M15

white light block with body/fixing collar with  
integral LED 230...240V 1NO+1NC



## Main

|                               |                                                                                                                                                                            |
|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range of product              | Harmony XB4                                                                                                                                                                |
| Product or component type     | Complete body/contact assembly and light block                                                                                                                             |
| Device short name             | ZB4                                                                                                                                                                        |
| Fixing collar material        | Zamak                                                                                                                                                                      |
| Sale per indivisible quantity | 1                                                                                                                                                                          |
| Head type                     | Standard                                                                                                                                                                   |
| Contacts type and composition | 1 NO + 1 NC                                                                                                                                                                |
| Contact operation             | Slow-break                                                                                                                                                                 |
| Connections - terminals       | Screw clamp terminals, $\leq 2 \times 1.5 \text{ mm}^2$ with cable end EN 60947-1<br>Screw clamp terminals, $\geq 1 \times 0.22 \text{ mm}^2$ without cable end EN 60947-1 |
| Light source                  | Protected LED                                                                                                                                                              |
| Bulb base                     | Integral LED                                                                                                                                                               |
| Light block supply            | Direct                                                                                                                                                                     |
| Light source colour           | White                                                                                                                                                                      |
| [Us] rated supply voltage     | 230...240 V AC 50/60 Hz                                                                                                                                                    |

## Complementary

|                                             |                                                                                                                                                                                                                                                                          |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CAD overall width                           | 1.18 in (30 mm)                                                                                                                                                                                                                                                          |
| CAD overall height                          | 1.85 in (47 mm)                                                                                                                                                                                                                                                          |
| Terminals description ISO n°1               | (11-12)NC                                                                                                                                                                                                                                                                |
| Net Weight                                  | 0.16 lb(US) (0.074 kg)                                                                                                                                                                                                                                                   |
| Contacts usage                              | Standard                                                                                                                                                                                                                                                                 |
| Positive opening                            | With EN/IEC 60947-5-1 appendix K                                                                                                                                                                                                                                         |
| Operating travel                            | 0.06 in (1.5 mm) NC changing electrical state<br>0.10 in (2.6 mm) NO changing electrical state<br>0.17 in (4.3 mm) total travel)                                                                                                                                         |
| Operating force                             | 2 N NC changing electrical state<br>2.3 N NO changing electrical state                                                                                                                                                                                                   |
| Operating torque                            | 0.44 lbf.in (0.05 N.m) NO changing electrical state                                                                                                                                                                                                                      |
| Mechanical durability                       | 5000000 cycles                                                                                                                                                                                                                                                           |
| Tightening torque                           | 7.08...10.62 lbf.in (0.8...1.2 N.m) EN 60947-1                                                                                                                                                                                                                           |
| Shape of screw head                         | Cross Philips no 1<br>Cross pozidriv No 1<br>Slotted flat Ø 4 mm<br>Slotted flat Ø 5.5 mm                                                                                                                                                                                |
| Contacts material                           | Silver alloy (Ag/Ni)                                                                                                                                                                                                                                                     |
| Short-circuit protection                    | 10 A cartridge fuse gG EN/IEC 60947-5-1                                                                                                                                                                                                                                  |
| [Ith] conventional free air thermal current | 10 A EN/IEC 60947-5-1                                                                                                                                                                                                                                                    |
| [Ui] rated insulation voltage               | 600 V 3)EN 60947-1                                                                                                                                                                                                                                                       |
| [Uimp] rated impulse withstand voltage      | 6 kV EN 60947-1                                                                                                                                                                                                                                                          |
| [Ie] rated operational current              | 3 A 240 V, AC-15, A600 EN/IEC 60947-5-1<br>6 A 120 V, AC-15, A600 EN/IEC 60947-5-1<br>0.1 A 600 V, DC-13, Q600 EN/IEC 60947-5-1<br>0.27 A 250 V, DC-13, Q600 EN/IEC 60947-5-1<br>0.55 A 125 V, DC-13, Q600 EN/IEC 60947-5-1<br>1.2 A 600 V, AC-15, A600 EN/IEC 60947-5-1 |

|                        |                                                                                                                                                                                                                                                                                                                                                                                                           |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Electrical durability  | 1000000 Cycles, AC-15, 2 A 230 V 3600 cyc/h 0.5 EN/IEC 60947-5-1 appendix C<br>1000000 Cycles, AC-15, 3 A 120 V 3600 cyc/h 0.5 EN/IEC 60947-5-1 appendix C<br>1000000 Cycles, AC-15, 4 A 24 V 3600 cyc/h 0.5 EN/IEC 60947-5-1 appendix C<br>1000000 Cycles, DC-13, 0.2 A 110 V 3600 cyc/h 0.5 EN/IEC 60947-5-1 appendix C<br>1000000 cycles, DC-13, 0.5 A 24 V 3600 cyc/h 0.5 EN/IEC 60947-5-1 appendix C |
| Electrical reliability | $\Lambda < 10\exp(-6)$ 5 V 1 mA in clean environment EN/IEC 60947-5-4<br>$\Lambda < 10\exp(-8)$ 17 V 5 mA in clean environment EN/IEC 60947-5-4                                                                                                                                                                                                                                                           |
| Signalling type        | Steady                                                                                                                                                                                                                                                                                                                                                                                                    |
| Supply voltage limits  | 195...264 V AC                                                                                                                                                                                                                                                                                                                                                                                            |
| Current consumption    | 14 mA                                                                                                                                                                                                                                                                                                                                                                                                     |
| Service life           | 100000 h at rated voltage and 25 °C                                                                                                                                                                                                                                                                                                                                                                       |
| Surge withstand        | 1 kV IEC 61000-4-5                                                                                                                                                                                                                                                                                                                                                                                        |
| Device presentation    | Basic sub-assemblies                                                                                                                                                                                                                                                                                                                                                                                      |

## Environment

|                                       |                                                                                                                                         |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Protective treatment                  | TH                                                                                                                                      |
| Ambient air temperature for storage   | -40...158 °F (-40...70 °C)                                                                                                              |
| Ambient air temperature for operation | -40...158 °F (-40...70 °C)                                                                                                              |
| Electrical shock protection class     | Class I IEC 60536                                                                                                                       |
| Standards                             | CSA C22.2 No 14<br>EN/IEC 60947-5-5<br>EN/IEC 60947-1<br>JIS C8201-5-1<br>EN/IEC 60947-5-4<br>EN/IEC 60947-5-1<br>UL 508<br>JIS C8201-1 |
| Product certifications                | CSA<br>BV<br>DNV<br>UL Listed<br>GL<br>LROS (Lloyds register of shipping)<br>RINA                                                       |
| Vibration resistance                  | 5 gn 2...500 Hz)IEC 60068-2-6                                                                                                           |
| Shock resistance                      | 30 gn 18 ms) half sine wave acceleration IEC 60068-2-27<br>50 gn 11 ms) half sine wave acceleration IEC 60068-2-27                      |
| Resistance to fast transients         | 2 kV IEC 61000-4-4                                                                                                                      |
| Resistance to electromagnetic fields  | 9.14 V/m (10 V/m) IEC 61000-4-3                                                                                                         |
| Resistance to electrostatic discharge | 6 KV on contact (on metal parts) IEC 61000-2-6<br>8 kV in free air (in insulating parts) IEC 61000-2-6                                  |
| Electromagnetic emission              | Class B IEC 55011                                                                                                                       |

## Ordering and shipping details

|                       |                                         |
|-----------------------|-----------------------------------------|
| Category              | 22469 - PUSHBUTTON,22MM ACCESSORIES-NEW |
| Discount Schedule     | CS2                                     |
| GTIN                  | 03389110893533                          |
| Nbr. of units in pkg. | 1                                       |
| Package weight(Lbs)   | 0.5 lb(US) (0.23 kg)                    |
| Returnability         | No                                      |
| Country of origin     | FR                                      |

## Packing Units

|                        |                  |
|------------------------|------------------|
| Unit Type of Package 1 | PCE              |
| Package 1 Height       | 2.32 in (5.9 cm) |
| Package 1 width        | 2.09 in (5.3 cm) |
| Package 1 Length       | 1.42 in (3.6 cm) |

## Offer Sustainability

|                            |                                                                                                                              |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                        |
| REACH free of SVHC         | Yes                                                                                                                          |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>                               |
| Mercury free               | Yes                                                                                                                          |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                          |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                                                       |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                                |
| Circularity Profile        | <a href="#">End Of Life Information</a>                                                                                      |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |


## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|



---

Dimensions

---



Panel Cut-out for Pushbuttons, Switches and Pilot Lights (Finished Holes, Ready for Installation)

| Connection by Screw Clamp Terminals or Plug-in Connectors or on Printed Circuit Board                                                                                                                                                                                                                                           | Connection by Faston Connectors                                                    |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|
|                                                                                                                                                                                                                                                |  |
| <p>(1) Diameter on finished panel or support</p> <p>(2) 40 mm min. / 1.57 in. min.</p> <p>(3) 30 mm min. / 1.18 in. min.</p> <p>(4) Ø 22.5 mm / 0.89 in. recommended (Ø 22.3 mm <math>_{0}^{+0.4}</math> / 0.88 in. <math>_{0}^{+0.016}</math>)</p> <p>(5) 45 mm min. / 1.78 in. min.</p> <p>(6) 32 mm min. / 1.26 in. min.</p> |                                                                                    |