



## Main

|                               |                             |
|-------------------------------|-----------------------------|
| Range of product              | Harmony XALF<br>Harmony XB5 |
| Product or component type     | Head for selector switch    |
| Device short name             | ZB5                         |
| Bezel material                | Dark grey plastic           |
| Mounting diameter             | 0.87 in (22 mm)             |
| Head type                     | Standard                    |
| Sale per indivisible quantity | 1                           |
| Shape of signaling unit head  | Round                       |
| Type of operator              | To centre spring return     |
| Operator profile              | Black standard handle       |
| Operator position information | 3 positions +/- 45°         |

## Complementary

|                             |                                                                                                                                                                                                                                                                                                               |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CAD overall width           | 1.14 in (29 mm)                                                                                                                                                                                                                                                                                               |
| CAD overall height          | 1.14 in (29 mm)                                                                                                                                                                                                                                                                                               |
| CAD overall depth           | 1.81 in (46 mm)                                                                                                                                                                                                                                                                                               |
| Net Weight                  | 0.04 lb(US) (0.017 kg)                                                                                                                                                                                                                                                                                        |
| Mechanical durability       | 1000000 cycles                                                                                                                                                                                                                                                                                                |
| Station name                | XALD 1...5 cut-outs<br>XALK 2...5 cut-outs                                                                                                                                                                                                                                                                    |
| Electrical composition code | C3 6 single front mounting<br>C4 6 single and double front mounting<br>C5 5 single front mounting<br>C6 5 single and double front mounting<br>C7 4 single front mounting<br>C8 4 single and double front mounting<br>C11 3 single front mounting<br>SF1 3 single front mounting<br>SR1 3 single rear mounting |
| Device presentation         | Basic element                                                                                                                                                                                                                                                                                                 |

## Environment

|                                       |                                               |
|---------------------------------------|-----------------------------------------------|
| Protective treatment                  | TH                                            |
| Ambient air temperature for storage   | -40...158 °F (-40...70 °C)                    |
| Ambient air temperature for operation | -40...158 °F (-40...70 °C)                    |
| Overvoltage category                  | Class II IEC 60536                            |
| IP degree of protection               | IP67 IEC 60529<br>IP69 IEC 60529<br>IP69K     |
| NEMA degree of protection             | NEMA 13<br>NEMA 4X                            |
| Resistance to high pressure washer    | 1015.26 psi (7000000 Pa) 131 °F (55 °C) 0.1 m |
| IK degree of protection               | IK06 IEC 50102                                |

|                        |                                                                                                                     |
|------------------------|---------------------------------------------------------------------------------------------------------------------|
| Standards              | UL 508<br>EN/IEC 60947-5-1<br>EN/IEC 60947-1<br>CSA C22.2 No 14<br>EN/IEC 60947-5-4<br>JIS C8201-5-1<br>JIS C8201-1 |
| Product certifications | UL Listed<br>RINA<br>GL<br>LROS (Lloyds register of shipping)<br>DNV<br>BV<br>CSA                                   |
| Vibration resistance   | 5 gn 2...500 Hz)IEC 60068-2-6                                                                                       |
| Shock resistance       | 30 gn 18 ms) half sine wave acceleration IEC 60068-2-27<br>50 gn 11 ms) half sine wave acceleration IEC 60068-2-27  |

## Ordering and shipping details

|                       |                                       |
|-----------------------|---------------------------------------|
| Category              | 22467 - PUSHBUTTONS,22MM(PLASTIC) NEW |
| Discount Schedule     | CS2                                   |
| GTIN                  | 00785901354857                        |
| Nbr. of units in pkg. | 1                                     |
| Package weight(Lbs)   | 0.04 lb(US) (0.02 kg)                 |
| Returnability         | Yes                                   |
| Country of origin     | FR                                    |

## Packing Units

|                              |                       |
|------------------------------|-----------------------|
| Unit Type of Package 1       | PCE                   |
| Package 1 Height             | 2.17 in (5.5 cm)      |
| Package 1 width              | 1.34 in (3.4 cm)      |
| Package 1 Length             | 2.13 in (5.4 cm)      |
| Unit Type of Package 2       | BB1                   |
| Number of Units in Package 2 | 5                     |
| Package 2 Weight             | 4.34 oz (123 g)       |
| Package 2 Height             | 2.17 in (5.5 cm)      |
| Package 2 width              | 10.43 in (26.5 cm)    |
| Package 2 Length             | 1.34 in (3.4 cm)      |
| Unit Type of Package 3       | S03                   |
| Number of Units in Package 3 | 200                   |
| Package 3 Weight             | 11.68 lb(US) (5.3 kg) |
| Package 3 Height             | 11.81 in (30 cm)      |
| Package 3 width              | 11.81 in (30 cm)      |
| Package 3 Length             | 15.75 in (40 cm)      |

## Offer Sustainability

|                            |                                                                                                |
|----------------------------|------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                          |
| REACH free of SVHC         | Yes                                                                                            |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a> |
| Toxic heavy metal free     | Yes                                                                                            |
| Mercury free               | Yes                                                                                            |
| RoHS exemption information | <a href="#">Yes</a>                                                                            |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                         |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                  |
| Circularity Profile        | <a href="#">End Of Life Information</a>                                                        |

Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|