Product data sheet Characteristics

ZB5AH063C0

blue flush illum pushbutton head for integral LED cp grey



Main

Range of product	Harmony XB5
Product or component type	Head for illuminated push-button
Product compatibility	Integral LED
Device short name	ZB5
Bezel material	Plastic colour plated grey
Mounting diameter	0.87 in (22 mm)
Head type	Standard
Sale per indivisible quantity	1
Shape of signaling unit head	Round
Type of operator	push-push
Operator profile	Blue flush, unmarked

Complementary

CAD overall width	1.14 in (29 mm)	
CAD overall height	1.14 in (29 mm)	
CAD overall depth	1.18 in (30 mm)	
Net Weight	0.04 lb(US) (0.017 kg)	
Mechanical durability	5000000 cycles	
Station name	XALD 15 cut-outs XALK 25 cut-outs	
Electrical composition code	M5 2 single front mounting integral LED M6 2 single front mounting integral LED and transformer M10 2 single front mounting integral LED MF1 2 single front mounting integral LED MR1 2 single rear mounting integral LED	
Device presentation	Basic element	-

Environment

Protective treatment	TH
Ambient air temperature for storage	-40158 °F (-4070 °C)
Ambient air temperature for operation	-13158 °F (-2570 °C)
Electrical shock protection class	Class II IEC 60536
IP degree of protection	IP66 IEC 60529 IP67 IEC 60529
NEMA degree of protection	NEMA 13 NEMA 4X
Resistance to high pressure washer	1015.26 psi (7000000 Pa) 131 °F (55 °C) 0.1 m
IK degree of protection	IK05 IEC 50102
Standards	EN/IEC 60947-5-1 CSA C22.2 No 14 EN/IEC 60947-5-5 EN/IEC 60947-5-4 EN/IEC 60947-1 JIS C8201-5-1 UL 508 JIS C8201-1

Product certifications	GL	
	CSA	
	LROS (Lloyds register of shipping)	
	BV	
	DNV	
	RINA	
	UL Listed	
Vibration resistance	5 gn 2500 Hz)IEC 60068-2-6	
Shock resistance	30 gn 18 ms) half sine wave acceleration IEC 60068-2-27	
	50 gn 11 ms) half sine wave acceleration IEC 60068-2-27	
Ordering and shipping details		
Ordering and shipping details Package weight(Lbs)	0.63 oz (18.000 g)	
	0.63 oz (18.000 g)	
	0.63 oz (18.000 g)	
Package weight(Lbs)	0.63 oz (18.000 g) 1.65 in (4.200 cm)	
Package weight(Lbs) Packing Units		
Package weight(Lbs) Packing Units Package 1 Height	1.65 in (4.200 cm)	
Package weight(Lbs) Packing Units Package 1 Height Package 1 width	1.65 in (4.200 cm) 1.30 in (3.300 cm)	

- · · · · ·	
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	€Yes
China RoHS Regulation	China RoHS Declaration