Product data sheet Characteristics

XVS72BMWN

Electronic Alarm NPN White





Main

TTT COLOR	
Range of product	Harmony XVS
Product or component type	Electronic alarm
Device short name	XVS

Complementary

White
ABS (acrylonitrile butadiene-styrene) body PC (polycarbonate) terminal cover
0.40 lb(US) (0.18 kg)
CE
Class II EN/IEC 61140
72 mm DIN rail
1224 V DC
0.8 kV
117 mA 12 V 125 mA 24 V 158 mA 12 V 200 mA 24 V
<= 1 x 1.5 mm²
2.83 in (72 mm)
2.83 in (72 mm)
2.73 in (69.3 mm)

Environment

Discrete output type	NPN	
Signalling type	16 tones alarm	
Standards	EN/IEC 61000-6-2 UL 464 EN/IEC 61000-6-3	
Product certifications	UR	
Protective treatment	TC	
Ambient air temperature for storage	-31158 °F (-3570 °C)	
Ambient air temperature for operation	14122 °F (-1050 °C)	
IP degree of protection	Panel mounted IP54 EN/IEC 60529	
Noise level	090 dB continuous or intermittent tone)1 m	

Ordering and shipping details

Category	22617 - XVC TOWER LIGHTS
Discount Schedule	XV
GTIN	00785901811190
Nbr. of units in pkg.	1
Package weight(Lbs)	0.59 lb(US) (0.27 kg)
Returnability	No
Country of origin	ID

Packing Units

Package 1 Height	1.040 dm
Package 1 width	0.940 dm
Package 1 Length	0.940 dm

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	☑ End Of Life Information	

Contractual warranty

Warranty	18 months

Product data sheet Dimensions Drawings

XVS72BMWN

Electronic Alarm

Dimensions

