8538SBW11V08

NEMA Combination Starter, Type S, nonfusible disconnect, Size 0, 18A, 5 HP at 600 VAC polyphase, 208 VAC coil, NEMA 4/4X



Main

Product	Combination Starter
Туре	S
Control Circuit Type	Common control circuit

Complementary

Starter Type Non reversing Number of Poles 3P Horsepower Rating 3 Hp 200 V AC, 3 phase 3 Hp 230 V AC, 3 phase 5 Hp 460 V AC, 3 phase 5 hp 575 V AC, 3 phase Maximum Voltage Rating 600 V AC Control Units No control units Pilot Light No indicator Auxiliary Contacts Without Thermal overload type Melting alloy 3 Disconnect Type Non-fusible disconnect switch NEMA size No reversing No phase 3 Hp 200 V AC, 3 phase 3 Hp 200 V AC, 3 phase 5 hp 575 V AC, 3 phase 5 hp 460 V AC Welting alloy 3 Disconnect Type Non-fusible disconnect switch	Control Circuit Voltage	208 V AC 60 Hz	
Horsepower Rating 3 Hp 200 V AC, 3 phase 3 Hp 230 V AC, 3 phase 5 Hp 460 V AC, 3 phase 5 hp 575 V AC, 3 phase 600 V AC Control Units No control units Pilot Light No indicator Auxiliary Contacts Without Thermal overload type Melting alloy 3 Disconnect Type Non-fusible disconnect switch	Starter Type	Non reversing	
3 Hp 230 V AC, 3 phase 5 Hp 460 V AC, 3 phase 5 hp 575 V AC, 3 phase Maximum Voltage Rating 600 V AC Control Units No control units Pilot Light No indicator Auxiliary Contacts Without Thermal overload type Melting alloy 3 Disconnect Type Non-fusible disconnect switch	Number of Poles	3P	
Control Units Pilot Light No indicator Auxiliary Contacts Without Thermal overload type Melting alloy 3 Disconnect Type Non-fusible disconnect switch	Horsepower Rating	3 Hp 230 V AC, 3 phase 5 Hp 460 V AC, 3 phase	
Pilot Light No indicator Auxiliary Contacts Without Thermal overload type Melting alloy 3 Disconnect Type Non-fusible disconnect switch	Maximum Voltage Rating	600 V AC	
Auxiliary Contacts Without Thermal overload type Melting alloy 3 Disconnect Type Non-fusible disconnect switch	Control Units	No control units	
Thermal overload type Melting alloy 3 Disconnect Type Non-fusible disconnect switch	Pilot Light	No indicator	
Disconnect Type Non-fusible disconnect switch	Auxiliary Contacts	Without	
	Thermal overload type	Melting alloy 3	
NEMA size 0	Disconnect Type	Non-fusible disconnect switch	
	NEMA size	0	

Environment

Enclosure Type	NEMA 4/4X stainless steel with external reset

Ordering and shipping details

2 1	0.000 0.000 0.000 0.000 0.000 0.000 0.000	
Category	21218 - 8538,39 W/STAINLESS ENCLOS	
Discount Schedule	CP1	_
GTIN	00785901517801	
Nbr. of units in pkg.	1	
Package weight(Lbs)	40 lb(US) (18.14 kg)	
Returnability	Yes	
Country of origin	MX	

Offer Sustainability

EU RoHS Directive	Under investigation
China RoHS Regulation	☑ China RoHS Declaration

Contractual warranty

Warranty	18 months	