

70-750E11-1

Socket, Legacy general purpose relay accessory, 3PDT, 12A, 300 V, 11 pins, lift terminals, 750/750H series



Main

Product range	Legacy
Product type	Socket
Product compatibility	Relay 750XCXR Relay 750XCXH Suppressor module 70-ASMM Diode 70-ASMD Signalling device 70-ASMLG Suppressor module 70-ASMR Jumper wire 16-750CBJ-1
Number of terminals	11
Switch function	3PDT
Contact composition	3 NO + 3 NC

Complementary

Line Rated Current	12 A
Rated voltage	300 V
Contact terminal arrangement	Separate
Connections - terminals	Lift terminalsflexible Lift terminalssolid
Tightening torque	0.8 N.m, AWG 14...AWG 12, copper
Fixing mode	By screw M3.5, M3.5 panel
Shape of screw head	Combination roundhead
Net Weight	3.00 oz (85 g)
Width	1.50 in (38 mm)
Depth	2.24 in (57 mm)

Environment

Ambient air temperature for storage	-40...221 °F (-40...105 °C)
Ambient temperature range - operational	-40...131 °F (-40...55 °C)
IP degree of protection	IP20
Flame retardance	UL94-V0
Product certifications	UL CSA CE RoHS

Ordering and shipping details

GTIN	03606480278013
------	----------------

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.