



## Main

Product or component type	Starter
Type	S
Control Circuit Type	Separate control circuit

## Complementary

Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Motor starter type	Non reversing
Current Rating	18 A
Number of Poles	3P
Number of Phases	3 phase
Horsepower Rating	3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC
Maximum Voltage Rating	600 V AC
Control Units	Selector switch (HAND-OFF-AUTO)
Thermal overload type	Melting alloy 3
Electrical connection	Screw clamp terminals
NEMA size	0
Maximum Height	12.13 in (308 mm)
Maximum Depth	6.46 in (164 mm)
Maximum Width	6.50 in (165 mm)

## Environment

Enclosure Type	NEMA 4X glass polyester
Product certifications	UL Listed CSA NEMA

## Ordering and shipping details

Category	21202 - 8502,36 S*R,S*T,S*W
Discount Schedule	CP1
Package weight(Lbs)	35.19 lb(US) (15.96 kg)
Returnability	No
Country of origin	MX

## Offer Sustainability

EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------