



### Main

|                     |                            |
|---------------------|----------------------------|
| Product             | Single Unit Manual Starter |
| Type                | F                          |
| Overload Relay Type | Melting alloy              |

### Complementary

|                       |                                                 |
|-----------------------|-------------------------------------------------|
| Current Rating        | 16 A                                            |
| Cable entry           | Without                                         |
| Horsepower Rating     | 1 Hp 115 V AC<br>1 Hp 230 V AC<br>1 hp 277 V AC |
| Voltage Rating        | 277 V AC                                        |
| Number of Poles       | 1P                                              |
| Control Unit          | Toggle switch                                   |
| Number of Phases      | 1 phase                                         |
| Pilot Light           | No indicator                                    |
| Reset                 | Manual                                          |
| Motor starter type    | Non reversing                                   |
| Electrical connection | Screw clamp terminals                           |
| Wire Gauge            | AWG 14...AWG 12 copper                          |
| Maximum Height        | 4.5 in (114.30 mm)                              |
| Maximum Width         | 2.75 in (69.85 mm)                              |
| Maximum Depth         | 2.19 in (55.63 mm)                              |

### Environment

|                        |                                                             |
|------------------------|-------------------------------------------------------------|
| Product certifications | UL listed file E42243 CCN NLRV<br>CSA LR25490 class 3211 05 |
| NEMA Enclosure Rating  | Not rated (flush plate) sheet steel standard size           |

### Ordering and shipping details

|                     |                          |
|---------------------|--------------------------|
| Category            | 21101 - 2510,2511,2512 F |
| Discount Schedule   | CP1                      |
| GTIN                | 00785901553809           |
| Package weight(Lbs) | 0.4 lb(US) (0.18 kg)     |
| Returnability       | Yes                      |
| Country of origin   | MX                       |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

|                       |                                        |
|-----------------------|----------------------------------------|
| REACH Regulation      | <a href="#">REACH Declaration</a>      |
| REACH free of SVHC    | Yes                                    |
| EU RoHS Directive     | Not compliant                          |
| China RoHS Regulation | <a href="#">China RoHS Declaration</a> |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|