



## Main

Range of product	Harmony XK
Product or component type	Complete joystick controller
Product specific application	Light hoisting applications

## Complementary

Device short name	XKB
Sale per indivisible quantity	1
Protective treatment	TC
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Ambient air temperature for operation	-4...158 °F (-20...70 °C)
Overvoltage category	Class I IEC 61140
IP degree of protection	IP54 IEC 60529 IP20 IEC 60529
Standards	CSA C22.2 No 14 UL 508 EN/IEC 60947-5-1
Product certifications	UL RRS CCC CSA
Contact code designation	A300 Q300
Operator position information	All positions
Operator profile	Handle with zero position mechanical interlock
Notch per direction	1...3 12°-20°-28° for each direction
Mechanical durability	1000000 cycles
Vibration resistance	6 gn 1...70 Hz)IEC 60068-2-6
Shock resistance	20 gn 11 ms) IEC 60068-2-27
Short-circuit protection	10 A cartridge fuse gG EN/IEC 60947-5-1
[Ith] conventional free air thermal current	10 A EN/IEC 60947-5-1 10 A CSA C22.2 No 14 10 A UL 508
[Ui] rated insulation voltage	500 V 3)IEC 60947-1

## Ordering and shipping details

Category	22474 - PUSHBUTTON,CRANE JOYSTICKS
Discount Schedule	I
GTIN	00785901945093
Nbr. of units in pkg.	1
Package weight(Lbs)	0.86 lb(US) (0.39 kg)
Returnability	No
Country of origin	FR

## Packing Units

Package 1 Height	8.27 in (21.000 cm)
Package 1 width	6.69 in (17.000 cm)
Package 1 Length	6.69 in (17.000 cm)

## Contractual warranty

Warranty	18 months
----------	-----------