

Main

Product or component type	Starter
Type	S
Control Circuit Type	Separate control circuit

Complementary

Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Motor starter type	Non reversing
Current Rating	18 A
Number of Poles	3P
Number of Phases	3 phase
Horsepower Rating	3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC
Maximum Voltage Rating	600 V AC
Control Units	No control units
Auxiliary Contacts	2 NO
Thermal overload type	Melting alloy 3
Electrical connection	Screw clamp terminals
NEMA size	0
Maximum Height	10.00 in (254 mm)
Maximum Depth	5.55 in (141 mm)
Maximum Width	5.98 in (152 mm)

Environment

Enclosure Type	NEMA 1 painted sheet steel
Product certifications	UL Listed NEMA CSA

Ordering and shipping details

Category	21191 - 8502,36 SA,SB(NOT S*R,T,W)
Discount Schedule	CP1
Package weight(Lbs)	6 lb(US) (2.72 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------