



Main

Range of product	Lexium P, T
Product or component type	Delta 3 robot
Device short name	P4
Design	Flat

Complementary

Number of axis	3...4
Work envelope	0.00...47.24 in (0...1200 mm) diameter 0.00...8.86 in (0...225 mm) vertical
Repeat accuracy	+/- 0.1 mm
Permanent permissible load	33.07 lb(US) (15 kg)
Maximum actuation speed	32.81 ft/s (10 m/s)
Maximum acceleration	328.08 Ft/S ² (100 m/s ²) at 1 kg 246.06 ft/s ² (75 m/s ²) at 1.5 kg
Net Weight	242.51 lb(US) (110 kg)
Range compatibility	Lexium SH3 motor Lexium 62 ILM

Environment

Environmental characteristic	Normal environment High pressure cleaner
------------------------------	---

Ordering and shipping details

Category	18357-PACDRIVE ROBOTIC
Discount Schedule	PC52
GTIN	03606485399065
Nbr. of units in pkg.	1
Package weight(Lbs)	255.74 lb(US) (116 kg)
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	47.24 in (120 cm)
Package 1 width	39.37 in (100 cm)
Package 1 Length	47.24 in (120 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes