



### Main

|                    |                    |
|--------------------|--------------------|
| Product            | Well-Guard Control |
| Type               | Class 8940 type SS |
| Device application | Pumping            |

### Complementary

|                         |                                                      |
|-------------------------|------------------------------------------------------|
| Control Circuit Type    | Common control circuit                               |
| Control Circuit Voltage | 240 V AC 60 Hz<br>220 V AC 50 Hz                     |
| Line Rated Current      | 27 A                                                 |
| Number of Poles         | 3                                                    |
| Horsepower Rating       | 7.5 hp 240 V AC, 3 phase                             |
| Maximum Voltage Rating  | 600 V AC                                             |
| Control Units           | Selector switch HAND-OFF-AUTO)<br>Push-button START) |
| Disconnect Type         | Fusible disconnect switch                            |
| Associated fuse rating  | 30 A                                                 |
| Fuse type               | H or K                                               |
| Thermal overload type   | Motor Logic solid state class 10/20                  |
| Protection type         | Overload<br>Phase loss<br>Phase unbalance            |
| Device mounting         | Surface                                              |
| Electrical connection   | Screw terminal                                       |
| NEMA size               | 1                                                    |
| Maximum Height          | 39.06 in (992 mm)                                    |
| Maximum Width           | 15.16 in (385 mm)                                    |
| Maximum Depth           | 9.69 in (246 mm)                                     |

### Environment

|                        |                                       |
|------------------------|---------------------------------------|
| NEMA Rating            | NEMA 3R                               |
| Enclosure type         | Weatherproof enclosure indoor/outdoor |
| Product certifications | UL Listed<br>NEMA                     |

### Ordering and shipping details

|                     |                         |
|---------------------|-------------------------|
| Category            | 21388 - 8940 NSC,NSD    |
| Discount Schedule   | CP1                     |
| GTIN                | 00785901011743          |
| Package weight(Lbs) | 25.42 kg (56.04 lb(US)) |
| Returnability       | No                      |
| Country of origin   | MX                      |

Offer Sustainability

|                           |                                                                                                                                                                                                                                                                       |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a> |
| REACH Regulation          | <a href="#">REACH Declaration</a>                                                                                                                                                                                                                                     |
| EU RoHS Directive         | Not compliant                                                                                                                                                                                                                                                         |
| China RoHS Regulation     | <a href="#">China RoHS Declaration</a>                                                                                                                                                                                                                                |

Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|