# Product data sheet Characteristics

# ATV61HU22M3T1LW

## 3HP230VATV61w/ Ionworksandconduitbox

Main		
Asynchronous motor control profile	Variable torque standard	
Device short name	ATV61	
Range of product	Altivar 61	

## Complementary

Line Rated Current	11 A	
	8 A 1 phase	
Cable entry	Type 1 conduit entry outdoor	
Communication port protocol	LonWorks	
	CANopen	
	Modbus	
Input voltage	208/240 V AC	
Keypad type	LCD keypad	
Maximum Horse Power Rating	3 Hp	
Ç	2 hp, 1 phase	
Motor power kW	2.2 KW	
	1.5 kW, 1 phase	
Phase	3 phase output	
	1 phase input	
	3 phase	
Output voltage	<= rated supply voltage	

#### Environment

EMC filter	Class A EMC filter integrated
IP degree of protection	IP20
NEMA degree of protection	No enclosure rating (open device)
Protective treatment	None

### Ordering and shipping details

Category	22136-ATV61 1/2 THRU 5 HP DRIVES
Discount Schedule	CP4C
Package weight(Lbs)	17.00 lb(US) (7.711 kg)
Returnability	No
Country of origin	ID

#### Contractual warranty

Warranty	18 months	