

SLA3400

FA/LA MOLDED CASE CIRCUIT BREAKER, 415/240V, 400A, 3P



Main

Product or component type	Circuit breaker
Range of product	Square D
Trip Unit Type	Thermal-magnetic
Rating Code	A

Complementary

Line Rated Current	400 A
Number of Poles	3P
Interrupt Rating	42 KA 120 V AC 42 KA 240 V AC 30 KA 480Y/277 V AC 30 KA 480 V AC 22 KA 600 V AC 10 KA 125 V DC 10 kA 250 V DC
[Ue] rated operational voltage	600 V AC 125 V DC 250 V DC
Mounting mode	I-Line
Electrical connection	Lugs load I-Line connection line
Wire Gauge	AWG 1...600 kcmil aluminium/copper)1 AWG 1...250 kcmil aluminium/copper)2
Terminal Type	AL400LA
Magnetic hold current	2000 A
Magnetic tripping current	4000 A
Maximum Height	12.6 in (320.04 mm)
Maximum Width	12.5 in (317.50 mm)
Maximum Depth	19.9 in (505.46 mm)
Tightening torque	115.06 Lbf.in (13 N.m) 0.07...0.47 in ² (42...304 mm ²) AWG 1...600 kcmil) 115.06 lbf.in (13 N.m) 0.07...0.20 in ² (42...127 mm ²) AWG 1...250 kcmil)

Environment

Product certifications	IEC CE
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

Category	00923 - IEC I-LINE MCCB'S
Discount Schedule	DE2
GTIN	00785901572152
Package weight(Lbs)	18.19 lb(US) (8.25 kg)
Returnability	Yes
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause Birth Defects or other reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Not applicable, out of EU RoHS legal scope

Contractual warranty

Warranty	18 months
----------	-----------