

Main

Product or component type	Starter
Type	S
Control Circuit Type	Control circuit transformer

Complementary

Control Circuit Voltage	208 V AC 60 Hz
Motor starter type	Non reversing
Current Rating	540 A
Number of Poles	3P
Number of Phases	3 phase
Horsepower Rating	150 HP 200 V AC 200 HP 230 V AC 400 HP 460 V AC 400 HP 575 V AC
Maximum Voltage Rating	600 V AC
Control Units	2 momentary push-buttons (START-STOP)
Pilot Light	Green indicator on incandescent push-to-test
Control Circuit Fusing	2 fuses (primary), 2 fuses (secondary)
Thermal overload type	Melting alloy 3
Electrical connection	Screw clamp terminals
NEMA size	6
Maximum Height	65.75 in (1670 mm)
Maximum Depth	13.15 in (334 mm)
Maximum Width	20.24 in (514 mm)

Environment

Enclosure Type	NEMA 1 painted sheet steel
Product certifications	CSA UL Listed NEMA

Ordering and shipping details

Category	21195 - 8502,36 SH,SJ(NOT S*R,T,W)
Discount Schedule	CP1
Package weight(Lbs)	170 lb(US) (77.11 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

EU RoHS Directive	Not compliant
-------------------	---------------

Contractual warranty

Warranty	18 months
----------	-----------