



Overview

Lead time	Special Order - Call for Quoted Lead Times
-----------	--

General

Provided equipment	EcoStruxure IT ready (UPS) Integrated network management
--------------------	---

Physical

Color	White
Maximum Depth	540.00 in (1371.6 cm)
Maximum Height	142.52 in (362 cm)
Net Weight	120000.00 lb(US) (54431.04 kg)
Number of racks	27
Rack Free Space	1134
Number of rack unit	42U
Maximum Width	236.42 in (600.5 cm)

Input

Input Frequency	60 Hz +/- 0.5 / 1 / 2 / 4 / 6 / 8 % programmable
Efficiency at full load	408...552 V adjustable 480 V 408...552 V 480 V
Nominal Input Voltage	3 phase
Number of input connectors	1 Hard Wire 4-wire (3PH + G)

Output

Kw Rating	190000 W
Bypass type	Internal Bypass (Automatic and Manual)
Crest factor	Unlimited
Output Frequency (sync to mains)	60 Hz sync to mains
KW per Rack	7 kW
Output voltage	208 V 3 phase
PDU Amp Capacity	16 A
PDU Type	Metered
Configured Power	190000 W
Waveform Type	Sine wave

Conformance

Product certifications	CUL Listed UL Listed
------------------------	-------------------------

Environmental

Ambient air temperature for operation	-13...104 °F (-25...40 °C)
Operating altitude	0...1500 ft

Batteries & Runtime

Battery Slots Empty	0
Included Battery Modules	0
Battery type	VRLA
Liquid Electrolyte Value	0
Battery Volt-Amp-Hour Capacity	0 VAh

Communications & Management

Emergency Power Off (EPO)	Optional
---------------------------	----------

Contractual warranty

Warranty	1 year (parts only)
----------	---------------------