



### Main

Product or component type	Straight length
Range of product	Powerbus

### Complementary

Line Rated Current	100 A
Busbar Configuration	4B L1 + IG + L2 + L3
Busbar Material	Silver plated copper busbar
Integral Ground	50 percent capacity integral ground bus
Voltage Rating	600 V AC
Number of Phases	3 phase
Wiring Configuration	3-wire
Length	10 ft (3.05 m)
Enclosure material	Painted aluminium Black
Number of openings	10 each side







### Environment

IP degree of protection	IP40
-------------------------	------

### Ordering and shipping details

Category	20171-NEW 100A & 225A POWERBUS
Discount Schedule	PE8
Package weight(Lbs)	32.00 lb(US) (14.515 kg)
Returnability	No

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP and DIDP which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	 <a href="#">End Of Life Information</a>