



## Main

|                               |                                      |
|-------------------------------|--------------------------------------|
| Range of product              | Harmony XB5                          |
| Product or component type     | Head for illuminated selector switch |
| Product compatibility         | Integral LED                         |
| Device short name             | ZB5                                  |
| Bezel material                | Plastic colour plated white          |
| Mounting diameter             | 0.87 in (22 mm)                      |
| Head type                     | Standard                             |
| Sale per indivisible quantity | 1                                    |
| Shape of signaling unit head  | Round                                |
| Type of operator              | Stay put                             |
| Operator profile              | Orange standard handle               |
| Operator position information | 2 positions 90°                      |

## Complementary

|                             |                                                                                                                                                                                                                                                                                             |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CAD overall width           | 1.14 in (29 mm)                                                                                                                                                                                                                                                                             |
| CAD overall height          | 1.14 in (29 mm)                                                                                                                                                                                                                                                                             |
| CAD overall depth           | 1.69 in (43 mm)                                                                                                                                                                                                                                                                             |
| Net Weight                  | 0.04 lb(US) (0.016 kg)                                                                                                                                                                                                                                                                      |
| Mechanical durability       | 1000000 cycles                                                                                                                                                                                                                                                                              |
| Station name                | XALD 1...5 cut-outs<br>XALK 2...5 cut-outs                                                                                                                                                                                                                                                  |
| Electrical composition code | M3 4 single front mounting integral LED<br>M6 2 single front mounting integral LED and transformer<br>M10 2 single front mounting integral LED<br>MF1 2 single front mounting integral LED<br>MR1 2 single rear mounting integral LED<br>M4 4 single and double front mounting integral LED |
| Device presentation         | Basic element                                                                                                                                                                                                                                                                               |

## Environment

|                                       |                                                                                                                                         |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Protective treatment                  | TH                                                                                                                                      |
| Ambient air temperature for storage   | -40...158 °F (-40...70 °C)                                                                                                              |
| Ambient air temperature for operation | -40...158 °F (-40...70 °C)                                                                                                              |
| Overvoltage category                  | Class II IEC 60536                                                                                                                      |
| IP degree of protection               | IP66 IEC 60529<br>IP67                                                                                                                  |
| NEMA degree of protection             | NEMA 13<br>NEMA 4X                                                                                                                      |
| Resistance to high pressure washer    | 1015.26 psi (7000000 Pa) 131 °F (55 °C) 0.1 m                                                                                           |
| IK degree of protection               | IK06 IEC 50102                                                                                                                          |
| Standards                             | EN/IEC 60947-5-5<br>EN/IEC 60947-1<br>JIS C8201-5-1<br>EN/IEC 60947-5-1<br>CSA C22.2 No 14<br>EN/IEC 60947-5-4<br>UL 508<br>JIS C8201-1 |

|                        |                                                                                                                    |
|------------------------|--------------------------------------------------------------------------------------------------------------------|
| Product certifications | BV<br>CSA<br>RINA<br>UL Listed<br>DNV<br>LROS (Lloyds register of shipping)<br>GL                                  |
| Vibration resistance   | 5 gn 2...500 Hz)IEC 60068-2-6                                                                                      |
| Shock resistance       | 30 gn 18 ms) half sine wave acceleration IEC 60068-2-27<br>50 gn 11 ms) half sine wave acceleration IEC 60068-2-27 |

## Ordering and shipping details

|                     |                    |
|---------------------|--------------------|
| Package weight(Lbs) | 0.85 oz (24.000 g) |
|---------------------|--------------------|

## Packing Units

|                  |                    |
|------------------|--------------------|
| Package 1 Height | 1.65 in (4.200 cm) |
| Package 1 width  | 1.30 in (3.300 cm) |
| Package 1 Length | 2.05 in (5.200 cm) |

## Offer Sustainability

|                            |                                                                                                                                                                                    |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| REACH free of SVHC         | Yes                                                                                                                                                                                |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)  <a href="#">EU RoHS Declaration</a> |
| Toxic heavy metal free     | Yes                                                                                                                                                                                |
| Mercury free               | Yes                                                                                                                                                                                |
| RoHS exemption information |  <a href="#">Yes</a>                                                                              |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>                                                         |