

Product data sheet

Characteristics

2601AW2

Switch, reversing drum, 2 HP at 230 VAC
single phase, 2 HP at 575 VAC polyphase,
handle operated, NEMA 4 enclosure



Main

Product	Reversing Drum Switch
Enclosure Rating	NEMA 4
Horsepower	1.5 Hp 115 V AC, 1 phase 2 Hp 230 V AC, 1 phase 2 Hp 200 V AC, 3 phase 2 Hp 230 V AC, 3 phase 2 Hp 460 V AC, 3 phase 2 Hp 575 V AC, 3 phase 0.25 Hp 115 V DC 0.25 hp 230 V DC
Maximum Rated Voltage	600 V AC 250 V DC
Number of Poles	3P

Complementary

Certifications	CSA UL Listed
Electrical Connection	Screw-clamp terminals
Type	A

Ordering and shipping details

Category	21116 - 2601
Discount Schedule	CP1
GTIN	00785901784432
Nbr. of units in pkg.	1
Package weight(Lbs)	2.74 lb(US) (1.24 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Package 1 Height	4.60 in (11.684 cm)
Package 1 width	5.60 in (14.224 cm)
Package 1 Length	7.90 in (20.066 cm)

Offer Sustainability

EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------