



Main

Product or component type	Shunt trip
Circuit breaker type	H-frame J-frame L-Frame

Complementary

Rated voltage	208...277 V AC
Tightening torque	12.39 lbf.in (1.4 N.m) 0.00...0.00 in ² (0.82...2.5 mm ²) AWG 18...AWG 14)

Environment

Product certifications	CSA
------------------------	-----

Ordering and shipping details

Category	01103 - H,J,COMPACT NS UL/IEC CIRCUIT BREAKER ACCESSORIES
Discount Schedule	DE2
GTIN	00785901545675
Nbr. of units in pkg.	1
Package weight(Lbs)	0.29 lb(US) (0.13 kg)
Returnability	Yes
Country of origin	US

Packing Units

Package 1 Height	1.70 in (4.318 cm)
Package 1 width	2.90 in (7.366 cm)
Package 1 Length	4.40 in (11.176 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP and DIDP which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty

18 months
