

Product data sheet

Characteristics

QO112L125PGRB

Load center, QO, 1 phase, 12 spaces, 12 circuits, 125A convertible main lugs, PoN, NEMA3R, grnd bar, UL



Main

Marketing Trade Name	QO
Product	Load Center
Enclosure type	Weatherproof enclosure
Provided equipment	Grounding bar

Complementary

Load Center Type	Main lugs
Line Rated Current	125 A
Number of spaces	12
Short Circuit Current Rating	65 kA
Maximum Number of Single Pole Circuits	12
Maximum Number of Tandem Breakers	12
Number of Phases	1 phase
Grounding Bar	Grounding bar included (not installed)
Box number	3R
Maximum Height	18.92 in (480.57 mm)
Maximum Width	14.75 in (374.65 mm)
Maximum Depth	4.52 in (114.81 mm)

Environment

Enclosure Rating	NEMA 3R outdoor
Ambient air temperature for operation	23 °F (-5 °C) 104 °F (40 °C)
Product certifications	UL Listed

Ordering and shipping details

Category	10002 - QO PON 1PH LC,12-60 CKT, N3R
Discount Schedule	DE3A
GTIN	00785901593621
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	Yes
Country of origin	US