



Main

Product or component type	Automatic switch
Range of product	PowerPact P
Trip unit technology	Magnetic
Accessory / separate part type	Rotary handle

Complementary

Line Rated Current	600 A
[Ue] rated operational voltage	480 V AC
Mounting mode	Unit mount
Poles description	3P
Short-circuit withstand	125 KA 240 V UL 489 100 kA 480 V UL 489
Breaking capacity code	L
Electrical connection	Lugs line Lugs load
AWG gauge	AWG 3/0...500 kcmil aluminium/copper)3
Terminal identifier	AL800M23K
Magnetic tripping current	10000 A
Maximum Height	16.24 in (412.50 mm)
Maximum Width	16.54 in (420.12 mm)
Maximum Depth	14.49 in (368.05 mm)
Tightening torque	442.54 lbf.in (50 N.m) 0.15...0.37 in ² (95...240 mm ²) AWG 3/0...500 kcmil)

Environment

Product certifications	CSA UL Listed IEC
------------------------	-------------------------

Ordering and shipping details

Category	01215 - PG,H,J,K,L,N UNIT MT BREAKERS
Discount Schedule	DE2
Package weight(Lbs)	32 lb(US) (14.51 kg)
Returnability	No
Country of origin	US

Contractual warranty

Warranty	18 months
----------	-----------