



## Main

Product	Adaptor
Range	I-Line

## Complementary

Rated Current	1350 A aluminium
Rated Operational Voltage	600 V AC/DC 50/60 Hz
Length	12 in (304.80 mm)
Material	Aluminium busbar
I-LINE Value End	Slot
Number of Phases	3 phase
For Use with	Busbar trunking 1350 A aluminium
Protection Type	50 percent capacity integral ground bus
Wiring Configuration	4-wire
Mounting Location	Indoor



## Environment

Standards	UL 857 CSA C22.2 No 27:1994 IEC 61439-6
-----------	---

## Ordering and shipping details

Category	20008-AF2/AFH2 1350A 4WIRE-COMM
Discount Schedule	PE8
GTIN	00785901159322
Package weight(Lbs)	37.59 lb(US) (17.051 kg)
Returnability	Yes
Country of origin	US

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds and Di-isodecyl phthalate (DIDP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
RECh Regulation	 <a href="#">RECh Declaration</a>
RECh free of SVHC	Yes
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes

Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

Contractual warranty

Warranty	18 months
----------	-----------