




Panel Thickness E dim. inches (mm)	Number of Gasket
1/16 (1.6)	4
1/8 (3.2)	3
3/16 (4.8)	2
1/4 (6.4)	1



Note:
- Drawings Not To Scale
- Drawings Subject to Change Without Notice
- Dimensions are inches next to [Millimeters]

Part No.:

9001SKR3L



Schneider Electric United States
North American Division
Boston One Campus
800 Federal Street
Andover, MA 01810, USA
Phone:+1 8773425173
Email: CCC@us.schneider-electric.com

Technical Information:

UL File:
CSA File:
CE Marked:
RoHS:
NEMA / IP Rating:
Key Number:
Key Removal:
Light Module Supply Voltage:
Light Module Type:
Number of Operators:

E78403 CCN NKCR
LR24590 Class 3211-03
Yes
Yes
NEMA 1/2/3/3R/4/4X/6/12/13 Water tight, Dust tight, Oil tight and Corrosion Resistant (Indoor/Outdoor)
n/a
n/a
not applicable
not applicable
1

Description:

Ring Nut Material:
Operator Type:
Operator Action:
Guard Type:
Button/Cap Color:
Lens Type:
Lens Color:
Knob Type:
Knob Color:
Number of Positions:

30mm Push Button
Black Plastic
Non-Illuminated
Momentary
Standard Pushbutton
No Guard
Blue
not applicable
not applicable
not applicable
n/a
2

Specification: