



## Main

Range of product	Harmony XB4 Harmony XB5
Product or component type	Light block
Device short name	ZBW
Connections - terminals	Screw terminals for lug
Signalling type	Steady
Light source	Incandescent
Bulb base	BA 9s
Light block supply	Integrated transformer 6 V
[Us] rated supply voltage	110...120 V AC 50/60 Hz

## Complementary

Current consumption	14 mA
Service life	100000 h at rated voltage and 25 °C
Surge withstand	1 kV IEC 61000-4-5

## Environment

Protective treatment	TH
Ambient air temperature for storage	-13...131 °F (-25...55 °C)
Ambient air temperature for operation	-13...158 °F (-25...70 °C)
IP degree of protection	IP20 IEC 60529
Standards	EN/IEC 60947-5-5 UL 508 EN/IEC 60947-1 JIS C8201-5-1 EN/IEC 60947-5-4 EN/IEC 60947-5-1 CSA C22.2 No 14 JIS C8201-1
Resistance to fast transients	2 kV IEC 61000-4-4
Resistance to electromagnetic fields	9.14 V/m (10 V/m) IEC 61000-4-3
Resistance to electrostatic discharge	6 KV on contact (on metal parts) IEC 61000-4-2 8 kV in free air (in insulating parts) IEC 61000-4-2
Electromagnetic emission	Class B IEC 55011

## Ordering and shipping details

GTIN	03389110177817
Package weight(Lbs)	0.02 lb(US) (0.010 kg)

## Packing Units

Package 1 Height	0.560 dm
Package 1 width	0.440 dm
Package 1 Length	0.540 dm

## Contractual warranty

Warranty	18 months
----------	-----------