



### Main

Range	TeSys
Product or component type	Specific contactor coil
Device short name	LX9FK
Range compatibility	TeSys F LC1F contactor TeSys F DR5TE rectifier
Product compatibility	LC1F500 DR5TE
Control circuit type	AC 40...400 Hz low consumption DC low consumption
[Uc] control circuit voltage	110 V AC 40...400 Hz 110 V DC
Average resistance	24 Ohm inrush 68 °F (20 °C) 204 Ohm holding 68 °F (20 °C)
Inductance of closed circuit	1.1 H
Operating time	60 ms opening 50 ms closing
Mechanical durability	10 Mcycles
Maximum operating rate	3600 cyc/h 158 °F (70 °C)

### Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	Operational 0.85...1.1 Uc 131 °F (55 °C) Drop-out 0.3...0.5 Uc 131 °F (55 °C)
Inrush power in VA	550 VA 40...400 Hz 68 °F (20 °C))
Hold-in power consumption in VA	31 VA 40...400 Hz 68 °F (20 °C))
Heat dissipation	15...18.3 W

### Environment

Ambient air temperature for operation	23...131 °F (-5...55 °C)
Net Weight	2.38 lb(US) (1.08 kg)

### Ordering and shipping details

Category	22341 - CONTACTOR,D,K,&F ACCESS
Discount Schedule	I12
GTIN	03389110083781
Nbr. of units in pkg.	1
Package weight(Lbs)	2.69 lb(US) (1.22 kg)
Returnability	No
Country of origin	CZ

### Packing Units

Package 1 Height	0.920 dm
Package 1 width	1.000 dm
Package 1 Length	1.860 dm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>

## Contractual warranty

Warranty	18 months
----------	-----------