



### Main

Range	9422T
Product	Disconnect Switch
Disconnect Type	Non-fusible disconnect switch

### Complementary

Mounting Type	Flange rod variable depth
Current Rating	400 A
Horsepower Rating	75 Hp 200 V AC 125 Hp 230 V AC 250 Hp 460 V AC 350 Hp 575 V AC 50 hp 250 V DC
Handle Type	Ordered separately

### Environment

Certifications	CSA UL Recognized
----------------	----------------------

### Ordering and shipping details

Category	21732 - 9422
Discount Schedule	CP1
GTIN	00785901728009
Package weight(Lbs)	45.09 lb(US) (20.45 kg)
Returnability	No
Country of origin	MX

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

### Contractual warranty

Warranty	18 months
----------	-----------