



### Main

Product or component type	Contactator
Range of product	TeSys N
Contactator application	Non-reversing
NEMA size	4
Maximum Horse Power Rating	40 Hp 200 V AC 50 Hp 230 V AC 100 Hp 460 V AC 100 hp 575 V AC
NEMA degree of protection	Not rated (open device)
Control circuit	Common control circuit
[Uc] control circuit voltage	240 V AC
Auxiliary contact composition	1 NO
Poles description	3P
Phase	3 phase
Line Rated Current	135 A
Product certifications	CSA CE UL Listed
[Ue] rated operational voltage	600 V AC
Electrical connection	Lugs

### Ordering and shipping details

Category	21197 - TESYS N CONTACTORS SIZES 3 - 7
Discount Schedule	CP1
Package weight(Lbs)	9.23 lb(US) (4.19 kg)
Returnability	No
Country of origin	CZ

### Offer Sustainability

EU RoHS Directive	Under investigation
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.