

# Product data sheet

## Characteristics

# 8903SZO19V02

Contactor, Type S, multipole lighting,  
mechanically held, 600A, 3 pole, 110/120 VAC  
50/60 Hz coil, open style



### Main

Product	Mechanically Held Lighting Contactor
Type	S

### Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	600 A
Number of Poles	3P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Electrical connection	Lugs
Maximum Height	20.98 in (533 mm)
Maximum Depth	10.51 in (267 mm)
Maximum Width	8.66 in (220 mm)

### Environment

Enclosure Type	Not rated (open device) surface none
Product certifications	UL Listed CSA

### Ordering and shipping details

Category	21324 - 8903 S (NOT S°C) MECH.
Discount Schedule	CP1
GTIN	00785901971641
Package weight(Lbs)	64 lb(US) (29.03 kg)
Returnability	No
Country of origin	MX

### Offer Sustainability

EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

### Contractual warranty

Warranty	18 months
----------	-----------