



Main

Product or component type	Starter
Type	S
Control Circuit Type	Common control circuit

Complementary

Control Circuit Voltage	220 V AC 50 Hz 240 V AC 60 Hz
Motor starter type	Non reversing
Current Rating	27 A
Number of Poles	2P
Number of Phases	1 phase
Horsepower Rating	3 HP 115 V AC 5 HP 230 V AC
Maximum Voltage Rating	600 V AC
Control Units	2 momentary push-buttons (START-STOP)
Thermal overload type	Melting alloy 1
Electrical connection	Screw clamp terminals
NEMA size	1P
Maximum Height	10.00 in (254 mm)
Maximum Depth	5.55 in (141 mm)
Maximum Width	5.98 in (152 mm)

Environment

Enclosure Type	NEMA 1 painted sheet steel
Product certifications	CSA UL Listed NEMA

Ordering and shipping details

Category	21192 - 8502,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901312680
Package weight(Lbs)	6 lb(US) (2.72 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------