GBX1200081404F

gearbox with straight teeth GBX- Ø 120 mm-reduction 8:1- < 8arcmin- 120 N.m



Main Range compatibility Lexium 32 Product or component Planetary gearbox type Gear box type Straight teeth Device short name GBX Gearbox external 4.72 in (120 mm) diameter Product compatibility BSH1404... Reduction ratio 8:1

Complementary

Complementary	
Maximum torsional backlash	8 arc.min
Torsional rigidity	12 N.m/arcmin
Housing colour	Black
Housing material	Black anodized aluminium
Shaft material	C 45
Additional information	Lubricated for life
Service life in hours	30000 h 100 rpm 86 °F (30 °C)
Efficiency	94 %
Maximum radial force Fr	1500 N 100 rpm, force applied at mid-distance from output shaft during 30000 hour at 30 °C 2000 N 100 rpm, force applied at mid-distance from output shaft during 10000 hour at 30 °C
Maximum axial force Fa	2100 N 100 rpm, during 30000 hour at 30°C 2800 N 100 rpm, during 10000 hour at 30°C
Continuous output torque	1062.09 lbf.in (120 N.m) 100 rpm 86 °F (30 °C)
Maximum output torque	1699.34 lbf.in (192 N.m) 100 rpm 86 °F (30 °C)
Net Weight	13.23 lb(US) (6 kg)

Environment

Noise level	65 dB 1 m, no-load
IP degree of protection	Shaft output IP54
Ambient temperature for operation	-13194 °F (-2590 °C)

Contractual warranty

Contractical Warranty		
Warranty	18 months	