ABE9C1280M

IP67 passive splitter box - with 8 channels M12 connector





Main

Range of product	Advantys ABE9	
Product or component type	IP67 passive splitter box	
Number of channels	8	
Electrical connection	1 male plug-in connector 8 female connectors M12 5 pins	
Status LED	without	

Complementary

Number of ways	16 ways	
[Ue] rated operational voltage	24 V DC	
Current per channel	4 A	
Insulation group	Category 3 VDE 0110	
Operating position	Any position	
Fixing mode	M4 screw fixing	
Contact resistance	5000 μOhm	
Current of common	16 A 0.00 in² (1 mm²) 12 A 0.00 in² (0.75 mm²)	
Separation of commons	Without or with	
Net Weight	0.22 lb(US) (0.1 kg)	

Environment

2.171.011.1011		
IP degree of protection	IP67 IEC 529	
Product certifications	CULus	
Ambient air temperature for operation	-4176 °F (-2080 °C)	
Ambient air temperature for storage	-40185 °F (-4085 °C)	
Vibration resistance	0.2 gn 57150 Hz)IEC 68-2-6, FC tests	
Shock resistance	30 gn 11 ms EN 68-2-2 30 gn 11 ms IEC 68-2-2	

Ordering and shipping details

Category	18125 - MODSOFT LITE SOFTWARE
Discount Schedule	PC12
GTIN	00785901521990
Nbr. of units in pkg.	1
Package weight(Lbs)	0.29 lb(US) (0.13 kg)
Returnability	No
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.57 in (4 cm)
Package 1 width	2.24 in (5.7 cm)
Package 1 Length	6.10 in (15.5 cm)
Unit Type of Package 2	S03
Number of Units in Package 2	60
Package 2 Weight	18.51 lb(US) (8.396 kg)
Package 2 Height	11.81 in (30 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability


Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and le compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov Yes	
REACh free of SVHC		
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	☑ End Of Life Information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	

Contractual warranty


Warranty	18 months	
	To monard	

ABE9C1280M

Dimensions with ABE9XCA18 •• Connector



Wiring Diagram



(1) BR1 and BR2: removable link

1/4 1 White 1/2 9 Grey/pink 2/4 2 Green 2/2 10 Red/blue 3/4 3 Yellow 3/2 11 White/green 4/4 4 Grey 4/2 12 Brown/green 5/4 5 Pink 5/2 13 White/yellow 6/4 6 Red 6/2 14 Yellow/brown 7/4 7 Black	
2/4 2 Green 2/2 10 Red/blue 3/4 3 Yellow 3/2 11 White/green 4/4 4 Grey 4/2 12 Brown/green 5/4 5 Pink 5/2 13 White/yellow 6/4 6 Red 6/2 14 Yellow/brown 7/4 Black	
2/2 10 Red/blue 3/4 3 Yellow 3/2 11 White/green 4/4 4 Grey 4/2 12 Brown/green 5/4 5 Pink 5/2 13 White/yellow 6/4 6 Red 6/2 14 Yellow/brown 7/4 Black	
3/4 3 Yellow 3/2 11 White/green 4/4 4 Grey 4/2 12 Brown/green 5/4 5 Pink 5/2 13 White/yellow 6/4 6 Red 6/2 14 Yellow/brown 7/4 Black	
3/2 11 White/green 4/4 4 Grey 4/2 12 Brown/green 5/4 5 Pink 5/2 13 White/yellow 6/4 6 Red 6/2 14 Yellow/brown 7/4 7 Black	
4/4 4 Grey 4/2 12 Brown/green 5/4 5 Pink 5/2 13 White/yellow 6/4 6 Red 6/2 14 Yellow/brown 7/4 7 Black	
4/2 12 Brown/green 5/4 5 Pink 5/2 13 White/yellow 6/4 6 Red 6/2 14 Yellow/brown 7/4 7 Black	
5/4 5 Pink 5/2 13 White/yellow 6/4 6 Red 6/2 14 Yellow/brown 7/4 7 Black	
5/2 13 White/yellow 6/4 6 Red 6/2 14 Yellow/brown 7/4 7 Black	
6/4 6 Red 6/2 14 Yellow/brown 7/4 7 Black	
6/2 14 Yellow/brown 7/4 7 Black	
7/4 7 Black	
7/2 15 White/grey	
8/4 Violet	
8/2 16 Grey/brown	
1, 3, 5 & 7/1 +1 Brown 1	
2, 4, 6 & 8/1 +2 Brown 2	
1, 3, 5 & 7/3 -1 Blue 1	
2, 4, 6 & 8/3 -2 Blue 2	
18/5 PE Green/yellow	

Connection Terminals

