

GUPXCB300EN540

GUTOR PXC UL Battery Cabinet, 300A Breaker, Premium 540 Watt/Cell Battery



Main

Ambient air temperature for operation	14...104 °F (-10...40 °C)
Ambient air temperature for storage	5...104 °F (-15...40 °C)
Battery design life	8...10 year(s)
Battery Placement	Battery Cabinet
Battery manufacturer	C&D and Enersys
Battery type	VRLA
Maximum Depth	31.50 in (80 cm)
Device mounting	Enclosed battery cabinet
Maximum Height	82.72 in (210.1 cm)
Manufacturing support	APC
Included Battery Modules	0
Battery Slots Empty	0
Operating altitude	0...9842 ft
Net Weight	4075.01 lb(US) (1848.39 kg)
Relative humidity	0...95 % non-condensing
Standards	FCC Part 15 class A UL 1778
Storage altitude	0...16404 ft (0.00...4999.94 m)
Maximum Width	39.69 in (100.8 cm)
Battery Volt-Amp-Hour Capacity	0 VAh
Mounting mode	Not rack-mountable

Ordering and shipping details

Package weight(Lbs)	4175.01 lb(US) (1893.75 kg)
---------------------	-----------------------------

Packing Units

Package 1 Height	90.71 in (230.4 cm)
Package 1 width	54.02 in (137.2 cm)
Package 1 Length	38.50 in (97.8 cm)
Number of Units in Package 3	1

Contractual warranty

Warranty	1 year (parts only)
----------	---------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.