8538SBG11V81CFF4P1TX11

NEMA Combination Starter, Type S, nonfusible disconnect, Size 0, 18A, 5 HP at 600 VAC polyphase, 120 VAC coil, NEMA 1



Main

Product	Combination Starter
Туре	S
Control Circuit Type	Control circuit transformer

Complementary

120 V AC 60 Hz secondary circuit	
480 V AC 60 Hz primary circuit	
Non reversing	
3P	
3 Hp 200 V AC, 3 phase	
· · · · · · · · · · · · · · · · · · ·	
5 hp 575 V AC, 3 phase	
600 V AC	
Selector switch HAND-OFF-AUTO)	
Red indicator on incandescent	
1 NO + 1 NC	
2 fuses primary circuit	
1 fuse secondary circuit	
Melting alloy 3	
Non-fusible disconnect switch	
0	
	480 V AC 60 Hz primary circuit Non reversing 3P 3 Hp 200 V AC, 3 phase 3 Hp 230 V AC, 3 phase 5 Hp 460 V AC, 3 phase 5 hp 575 V AC, 3 phase 600 V AC Selector switch HAND-OFF-AUTO) Red indicator on incandescent 1 NO + 1 NC 2 fuses primary circuit 1 fuse secondary circuit Melting alloy 3 Non-fusible disconnect switch

Environment

Enclosure Type	NEMA 1 painted sheet steel with external reset

Ordering and shipping details

Category	21212 - 8538,39SB(NOT S*R,S*T,S*W)	
Discount Schedule	CP1	
GTIN	00785901019664	
Nbr. of units in pkg.	1	
Package weight(Lbs)	39.44 lb(US) (17.89 kg)	
Returnability	No	
Country of origin	MX	

Offer Sustainability

EU RoHS Directive	Not compliant

Warranty 18 months