ZB5AL2

black projecting pushbutton head Ø22 spring return unmarked





Main

Range of product	Harmony XB5
Product or component type	Head for non-illuminated push-button
Device short name	ZB5
Bezel material	Dark grey plastic
Mounting diameter	0.87 in (22 mm)
Head type	Standard
Sale per indivisible quantity	1
Shape of signaling unit head	Round
Type of operator	Spring return
Operator profile	Black projecting, unmarked

Complementary

Device presentation	Basic element	
	SR1 3 single rear mounting	
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	SF1 3 single front mounting	
	C15 1 single front mounting	
	C11 3 single front mounting	
	C2 9 single and double front mounting	
Electrical composition code	C1 9 single front mounting	
	XALK 25 cut-outs	
Station name	XALD 15 cut-outs	
Mechanical durability	10000000 cycles	
Net Weight	0.04 lb(US) (0.019 kg)	
CAD overall depth	1.30 in (33 mm)	
CAD overall donth	1 20 in (22 mm)	
CAD overall height	1.14 in (29 mm)	
CAD overall width	1.14 in (29 mm)	

Environment

Environment	
Protective treatment	TH
Ambient air temperature for storage	-40158 °F (-4070 °C)
Ambient air temperature for operation	-40158 °F (-4070 °C)
Overvoltage category	Class II IEC 60536
IP degree of protection	IP66 IEC 60529 IP67 IP69 IP69K
NEMA degree of protection	NEMA 13 NEMA 4X
Resistance to high pressure washer	1015.26 psi (7000000 Pa) 131 °F (55 °C) 0.1 m
IK degree of protection	IK03 IEC 50102
Standards	EN/IEC 60947-5-4 EN/IEC 60947-5-1 JIS C8201-5-1 UL 508 EN/IEC 60947-1 CSA C22.2 No 14 JIS C8201-1

Product certifications	DNV	
	UL Listed	
	CSA	
	RINA	
	LROS (Lloyds register of shipping)	
	GL	
	BV	
Shock resistance	30 gn 18 ms) half sine wave acceleration IEC 60068-2-27	
	50 gn 11 ms) half sine wave acceleration IEC 60068-2-27	
Vibration resistance	5 gn 2500 Hz)IEC 60068-2-6	

Ordering and shipping details

Category	22467 - PUSHBUTTONS,22MM(PLASTIC) NEW	
Discount Schedule	CS2	
GTIN	00785901906384	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.04 lb(US) (0.02 kg)	
Returnability	Yes	
Country of origin	FR	

Packing Units

r doking office	
Unit Type of Package 1	PCE
Package 1 Height	1.34 in (3.4 cm)
Package 1 width	1.77 in (4.5 cm)
Package 1 Length	2.13 in (5.4 cm)
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Weight	2.40 lb(US) (1.09 kg)
Package 2 Height	1.34 in (3.4 cm)
Package 2 width	1.77 in (4.5 cm)
Package 2 Length	10.43 in (26.5 cm)
Unit Type of Package 3	S03
Number of Units in Package 3	150
Package 3 Weight	6.97 lb(US) (3.16 kg)
Package 3 Height	11.81 in (30 cm)
Package 3 width	11.81 in (30 cm)
Package 3 Length	15.75 in (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

	y	
Warranty	18 months	