

Main

| | |
|---------------------------|--------------------------|
| Product or component type | Starter |
| Type | S |
| Control Circuit Type | Separate control circuit |

Complementary

| | |
|-------------------------|---|
| Control Circuit Voltage | 110 V AC 50 Hz 120 V AC 60 Hz |
| Motor starter type | Non reversing |
| Current Rating | 270 A |
| Number of Poles | 3P |
| Number of Phases | 3 phase |
| Horsepower Rating | 75 HP 200 V AC 100 HP 230 V AC 200 HP 460 V AC 200 HP 575 V AC |
| Maximum Voltage Rating | 600 V AC |
| Control Units | No control units |
| Auxiliary Contacts | 1 NO + 1 NC |
| Thermal overload type | Solid state Motor Logic class 10 |
| Electrical connection | Screw clamp terminals |
| NEMA size | 5 |
| Maximum Height | 47.01 in (1194 mm) |
| Maximum Depth | 13.43 in (341 mm) |
| Maximum Width | 17.20 in (437 mm) |

Environment

| | |
|------------------------|-----------------------------|
| Enclosure Type | NEMA 12 painted sheet steel |
| Product certifications | NEMA CSA UL Listed |

Ordering and shipping details

| | |
|---------------------|------------------------------------|
| Category | 21194 - 8502,36SG(NOT S*R,S*T,S*W) |
| Discount Schedule | CP1 |
| Package weight(Lbs) | 190 lb(US) (86.18 kg) |
| Returnability | No |

Offer Sustainability

| | |
|-----------------------|--|
| EU RoHS Directive | Not compliant |
| China RoHS Regulation |  China RoHS Declaration |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|