



## Main

|                               |                                                    |
|-------------------------------|----------------------------------------------------|
| Range of product              | Harmony XB4                                        |
| Product or component type     | Head for triple-headed push-button                 |
| Device short name             | ZB4                                                |
| Bezel material                | Black metal                                        |
| Mounting diameter             | 0.87 in (22 mm)                                    |
| Sale per indivisible quantity | 1                                                  |
| Head type                     | Standard                                           |
| Shape of signaling unit head  | Rectangular                                        |
| Type of operator              | Spring return                                      |
| Operator profile              | 2 flush - 1 central projecting STOP push-buttons   |
| Operators description         | White "up arrow" - black "down arrow" - red "STOP" |

## Complementary

|                                    |                                                                                                    |
|------------------------------------|----------------------------------------------------------------------------------------------------|
| Net Weight                         | 0.12 lb(US) (0.056 kg)                                                                             |
| Resistance to high pressure washer | 1015.26 psi (7000000 Pa) 131 °F (55 °C) 0.1 m                                                      |
| Colour of marking                  | White marking when green, red or black caps<br>Black marking when white caps                       |
| Operator profile                   | Red projecting, STOP white)<br>White flush, up arrow black)<br>Black flush, down arrow white)      |
| Mechanical durability              | 1000000 cycles                                                                                     |
| Electrical composition code        | C1 9 single front mounting<br>C2 9 single and double front mounting<br>C11 3 single front mounting |
| Device presentation                | Basic element                                                                                      |

## Environment

|                                       |                                                                                                                                         |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Ambient air temperature for storage   | -40...158 °F (-40...70 °C)                                                                                                              |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C)                                                                                                              |
| Electrical shock protection class     | Class I IEC 60536                                                                                                                       |
| IP degree of protection               | IP69 IEC 60529<br>IP69K IEC 60529                                                                                                       |
| NEMA degree of protection             | NEMA 13<br>NEMA 4X                                                                                                                      |
| IK degree of protection               | IK06 IEC 50102                                                                                                                          |
| Standards                             | JIS C8201-5-1<br>EN/IEC 60947-1<br>EN/IEC 60947-5-1<br>UL 508<br>EN/IEC 60947-5-4<br>EN/IEC 60947-5-5<br>CSA C22.2 No 14<br>JIS C8201-1 |
| Product certifications                | LROS (Lloyds register of shipping)<br>UL Listed<br>RINA<br>BV<br>GL<br>DNV<br>CSA                                                       |

|                      |                                                                                                                    |
|----------------------|--------------------------------------------------------------------------------------------------------------------|
| Vibration resistance | 5 gn 2...500 Hz)IEC 60068-2-6                                                                                      |
| Shock resistance     | 30 gn 18 ms) half sine wave acceleration IEC 60068-2-27<br>50 gn 11 ms) half sine wave acceleration IEC 60068-2-27 |

## Ordering and shipping details

|                       |                |
|-----------------------|----------------|
| GTIN                  | 03389119603577 |
| Nbr. of units in pkg. | 1              |
| Package weight(Lbs)   | 1.98 oz (56 g) |

## Packing Units

|                        |                  |
|------------------------|------------------|
| Unit Type of Package 1 | PCE              |
| Package 1 Height       | 1.77 in (4.5 cm) |
| Package 1 width        | 1.30 in (3.3 cm) |
| Package 1 Length       | 2.09 in (5.3 cm) |

## Offer Sustainability

|                            |                                                                                                |
|----------------------------|------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                          |
| REACH free of SVHC         | Yes                                                                                            |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a> |
| Toxic heavy metal free     | Yes                                                                                            |
| Mercury free               | Yes                                                                                            |
| RoHS exemption information | <a href="#">Yes</a>                                                                            |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                         |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                  |
| Circularity Profile        | <a href="#">End Of Life Information</a>                                                        |

## Contractual warranty


|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

---


Dimensions

---

Without Boot



With Boot ZBA709



Panel Cut-out for Pushbuttons, Switches and Pilot Lights (Finished Holes, Ready for Installation)

| Connection by Screw Clamp Terminals or Plug-in Connectors or on Printed Circuit Board                                                                                                                                                                                           | Connection by Faston Connectors |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
|                                                                                                                                                                                                                                                                                 |                                 |
| (1) Diameter on finished panel or support<br>(2) 40 mm min. / 1.57 in. min.<br>(3) 30 mm min. / 1.18 in. min.<br>(4) Ø 22.5 mm / 0.89 in. recommended (Ø 22.3 mm $_{0}^{+0.4}$ / 0.88 in. $_{0}^{+0.016}$ )<br>(5) 45 mm min. / 1.78 in. min.<br>(6) 32 mm min. / 1.26 in. min. |                                 |

Pushbuttons, Switches and Pilot Lights for Printed Circuit Board Connection

Panel Cut-outs (Viewed from Installer's Side)



### Printed Circuit Board Cut-outs (Viewed from Electrical Block Side)

Dimensions in mm



A: 30 mm min.

B: 40 mm min.

Dimensions in in.



A: 1.18 in. min.

B: 1.57 in. min.

## General Tolerances of the Panel and Printed Circuit Board

The cumulative tolerance must not exceed 0.3 mm / 0.012 in:  $T1 + T2 = 0.3 \text{ mm max.}$

## Installation Precautions

- Minimum thickness of circuit board: 1.6 mm / 0.06 in.
- Cut-out diameter: 22.4 mm  $\pm$  0.1 / 0.88 in.  $\pm$  0.004
- Orientation of body/fixing collar ZB4 BZ009:  $\pm 2^{\circ} 30'$  (excluding cut-outs marked a and b).
- Tightening torque of screws ZBZ 006: 0.6 N.m (5.3 lbf.in) max.
- Allow for one ZB4 BZ079 fixing collar/pillar and its fixing screws:
  - every 90 mm / 3.54 in. horizontally (X), and 120 mm / 4.72 in. vertically (Y).
  - with each selector switch head (ZB4 BD\*, ZB4 BJ\*, ZB4 BG\*).

The fixing centers marked a and b are diagonally opposed and must align with those marked 4 and 5.



- (1) Panel  
(2) Printed circuit board

### Mounting of Adapter (Socket) ZBZ 01•

- 1 2 elongated holes for ZBZ 006 screw access
- 2 1 hole  $\varnothing 2.4 \text{ mm} \pm 0.05 / 0.09 \text{ in.} \pm 0.002$  for centring adapter ZBZ 01•
- 3 8 ×  $\varnothing 1.2 \text{ mm} / 0.05 \text{ in.}$  holes
- 4 1 hole  $\varnothing 2.9 \text{ mm} \pm 0.05 / 0.11 \text{ in.} \pm 0.002$ , for aligning the printed circuit board (with cut-out marked a)
- 5 1 elongated hole for aligning the printed circuit board (with cut-out marked b)
- 6 4 holes  $\varnothing 2.4 \text{ mm} / 0.09 \text{ in.}$  for clipping in adapter ZBZ 01•

Dimensions An + 18.1 relate to the  $\varnothing 2.4 \text{ mm} \pm 0.05 / 0.09 \text{ in.} \pm 0.002$  holes for centring adapter ZBZ 01•.

---

Electrical Composition Corresponding to Code C1

---



---

Electrical Composition Corresponding to Code C2

---



---

Electrical Composition Corresponding to Codes C9, C11, SF1 and SR1

---



---

Legend

---

Single contact



Double contact



Light block



Possible location

