



### Main

Product or component type	Industrial Control Transformer
Power Rating	750 VA
Primary Voltage	208 V
Secondary Voltage	120 V
Type	TF

### Complementary

Number of Phases	1 phase
Power Rating	750 VA UL 750 VA CSA 750 VA NOM 500 VA
Primary to Secondary Voltage	208 V 120 V
Fuse type	0.41 x 1.50 in CC top
Temperature rise	115 °C
Electrical connection	Screw clamp terminals
Maximum Height	5.8 in (147.32 mm)
Maximum Width	5.25 in (133.35 mm)
Maximum Depth	5.61 in (142.49 mm)
Material	Copper winding
Fingersafe Cover Compatibility	FSC2

### Environment

Product certifications	UL listed file E61239 CSA file LR37055 guide 184-N-90
Enclosure Type	Not rated (open device)
Insulation temperature	356 °F (180 °C)

### Ordering and shipping details

Category	16203 - 9070 TF (NOT T) 250-1000VA
Discount Schedule	CP8
GTIN	00785901314516
Nbr. of units in pkg.	1
Package weight(Lbs)	17.3 lb(US) (7.85 kg)
Returnability	No
Country of origin	US

### Packing Units

Package 1 Height	7.00 in (17.780 cm)
Package 1 width	9.00 in (22.860 cm)
Package 1 Length	9.00 in (22.860 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------